

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR ARCO Oil & Gas Company
Division of Atlantic Richfield Company

3. ADDRESS OF OPERATOR
P. O. Box 1710, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1810' FNL & 2164' FWL Unit "F"

AT TOP PROD. INTERVAL: As above

AT TOTAL DEPTH: As above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

APR 29 1981

U.S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

(other) Spud, set Conductor & Surf pipe, Cmt

5. LEASE
LC-055546

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Custer Wells

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
Custer Ellenburger/Devonian

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
6-25S-37E

12. COUNTY OR PARISH
Lea

13. STATE
N M

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3239.1' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 4/15/81 drilled to 39' & set 20" conductor csg @ 39'. Cmt'd w/3 yds Redi-mix. Spudded 17½" hole @ 12:00 noon, 4/18/81. Drld to 1164'. RIH w/ 195.48' of 13-3/8" OD 61# K-55 csg & 978.17' of 13-3/8" OD 54# K-55 csg, set @ 1164'. FC set @ 1095'. Cmt'd 13-3/8" OD csg w/858 sx Cl C cmt cont'g 4% gel & 2% CaCl₂, followed by 200 sx Cl C cmt w/2% CaCl₂. Circ 300 sx cmt to surf. WOC 27 hrs. Drilled out cmt & FC @ 1095', cmt to 1144'. Press tested csg to 1000# for 30 mins, OK.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. J. Williams TITLE Dist. Drlg. Supt DATE 4/23/81

ACCEPTED FOR RECORD (This space for Federal or State office use)	
ROGER A. CHAPMAN	
APPROVED BY	TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:	
MAY 4 1981	
U.S. GEOLOGICAL SURVEY	
ROSWELL, NEW MEXICO	

*See Instructions on Reverse Side