

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

NM 14813

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Doeskin Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Dollarhide-Tubb Drinkard

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 18, T24S, R38E

12. COUNTY OR PARISH

Lea

13. STATE

N. M.

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER Plugged and Abandoned

2. NAME OF OPERATOR

Alpha Twenty-One Production Company

3. ADDRESS OF OPERATOR

2100 First National Bank Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

2310 FWL and 2310 FNL, Section 18, T24S, R38E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3189 Ground Level

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☒

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)


17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

This well was Plugged and Abandoned using the Following Procedure:

Place 150' Cement Plug Across Top of Drinkard (6375'-6525')  
Place 150' Cement Plug Across Top of Glorietta (5295'-5445')  
Place 100' Cement Plug Across Top of Queen (3550'-3650')  
Place 100' Cement Plug Across Base of Salt (2650'-2750')  
Place 100' Cement Plug Across 8-5/8" Casing Shoe (1240'-1340')  
Place 15 Sacks Cement Plug at the Surface  
Erect Monument at the Wellsite

Plugging Work was Completed on 8-7-81. Location will be cleaned when Pits dry up.

(Oral Permission to P&A received from USGS Representative, Roger A. Chapman on 8-4-81)



OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Tommy Phillips

TITLE Executive Vice President

DATE 8-12-81

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

NOV 3 1981

FOR

JAMES A. GILHAM  
DISTRICT SUPERVISOR

\*See Instructions on Reverse Side