

N. M. OIL CONS. COMMISSION
UNITED STATES P. O. BOX 1980
DEPARTMENT OF THE INTERIOR HOBBS, NEW MEXICO 88240
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
CONOCO INC.
3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA


5. LEASE
LC-032581(a)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
NMFU
8. FARM OR LEASE NAME
Sholes A Ac/1
9. WELL NO.
5
10. FIELD OR WILDCAT NAME
Undesignated (G/SA)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 24, T-25S, R-36E
12. COUNTY OR PARISH
Lea
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) perforation record

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐
☐



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1/11/82: Perfed Goat Seep Reef at 3693', 95', 3706', 12', 14', 21', 26' w/ 1 JS PF. Acidized w/ 700 gals. 15% HCL-NE-FE. Flushed w/ 3466ls. 2% KCL-TFW. Squeezed w/ 80sx Class C cmt. Cmt retainer at 3676' w/ 10' cmt on top. 1/15/82: Perfed Grayburg at 3555', 58', 60', 62', 71', 82', 84', 94', 97', 3626', 41', 42' w/ 1 JS PF. Squeezed w/ 75sx Class C cmt. Cmt retainer at 3540'. 1/21/82: Perfed Queen at 3380', 82', 90', 3461', 69', 72', 75', 97', 98', 3524' w/ 1 JS PF. Squeezed w/ 50sx Class C cmt retainer at 3334' w/ 10' cmt on top. Perfed 5 1/2" csg. at 2990' & 2602'.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED W. A. D. Butcher TITLE Administrative Supervisor

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

ACCEPTED FOR RECORD
MAY 4 1982
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

Squeezed w/ 2005X Class Cement w/ cement retainer at 2553' w/ 10' cement on top. Drilled out cement and retainer to FBTD of 3334'. Perforated Seven Rivers at 3016', 18', 60', 63', 69', 72', 3142', 61', 95', 3297' w/ 1535F on 1/28/82. Squeezed w/ 1005X Class Cement. Cement retainer at 3000'. Poot w/ tubing. Wellbore to be filled w/ polymer fluid. Well temporarily abandoned. All zones tested water.

RECEIVED

MAY 6 1982

U.S. DEPT. OF THE INTERIOR
NATURAL RESOURCES SERVICE