

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-76

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-1327	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEFEED OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT TO DRILL OR TO DEFEED OR PLUG BACK TO A DIFFERENT RESERVOIR."

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name -----
Name of Operator MORRIS R. ANTWEIL		8. Farm or Lease Name Eagle
Address of Operator P. O. Box 2010 Hobbs, New Mexico 88240		9. Well No. 1
Location of Well UNIT LETTER J 2310 FEET FROM THE South LINE AND 1650 FEET FROM THE East LINE, SECTION 36 TOWNSHIP 25-S RANGE 36-E N.M.P.M.		10. Field and Pool, or Wildcat Jalmat
15. Elevation (Show whether DF, RT, GR, etc.) 2981' GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7 7/8" hole to 2966' TD. Ran 4 1/2" 10.5# J-55 casing and cemented at 2966' with 900 sx Halliburton Lite containing 10 #/sk gilsonite and 1/4 #/sk Flocele and 250 sx 50-50 Pozmix/ Class C cement containing 2% gel, 1/4 #/sk Flocele and 2% CaCl2. Plug down at 6:30 AM 11 Oct 81. Circulated cement. Will test casing when completion operations begin.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Jerry Miller</u>	TITLE <u>Agent</u>	DATE <u>14 Oct 81</u>
APPROVED BY <u>Oct 14 1981</u>	TITLE <u></u>	DATE <u></u>
CONDITIONS OF APPROVAL, IF ANY:		