(Other)

## UNITED STATES DEPARTMENT F THE INTERIOR (Other Instructions of Control of Contro


SUBMIT IN TRIPLICAME.

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

	GEOLOGICAL SURVEY	MC-032579		
	SUNDRY NOTICES AND REPORTS ON WALLS OF AND	6. IF INDIAN, ALLOTTEE	OR TRIBE NAME	
	SUNDRY NOTICES AND REPORTS ON WALLS  (Do not use this form for proposals to drill or to deepen or plug back that different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)  OIL WELL GAS WELL OTHER  NAME OF OPERATOR			
i .	OIL M GAS D	7. UNIT AGREEMENT NA	ME	
	WELL WELL OTHER			
2.	NAME OF OPERATOR	8. FARM OR LEASE NAM		
	MORRIS R. ANTWEIL	UNION FEDERAL		
3.	ADDRESS OF OPERATOR	9. WELL NO.		
	Box 2010, Hobbs, New Mexico 88240	1		
<b>1</b> .	LOCATION OF WELL (Report location clearly and in accordance with any State requirements.	10. FIELD AND POOL, OR WILDCAT		
	See also space 17 below.) At surface	Langlie Mat	tix-7R,Q-6b	
	1980'FNL and 330' FEL of Section 27	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA		
		Sec. 27,T25S,R37E		
		Dec. 27,1230,R37E		
14.	PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH   13. STATE		
	3031.4	Lea	N.M.	
6.	Check Appropriate Box To Indicate Nature of Notice, Report, or O	ther Data		
	NOTICE OF INTENTION TO:	ENT REPORT OF:		
	TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF	REPAIRING W	ELL	
	FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT	ALTERING CA	SING	
	SHOOT OR ACIDIZE ABANDON* SHOOTING OR ACIDIZING	ABANDONMEN		
	REPAIR WELL CHANGE PLANS (Other) Cement Ca	sing		

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

> Drill 7-7/8" hole to 3375' TD. Run 4-1/2" 10.5#/ft J-55 casing and cemented at 3375' with 400 sx. Halliburton Light cement containing 5#/sx gilsonite and 1/4#/sk Flocele, 400 sx Halliburton Light with 1/4#/sk Flocele and 250 sx 50/50 pozmix/Class C containing 2% gel, 1/4#/sk Flocele and 2% CaCl<sub>2</sub>. Plug down 3:00 PM 7 January, 1982. Circulated cement. Will test casing when completion operations begin.



OIE & CAS U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO

	ACCEPTED FOR RECORD					
18. I here SIGNI	ED July Hellow	TITLE	Agent	DATE	8 Jan.,	1982
(This	space for Fed Alber State local use)					
APPR	OVED BY  ONE OF GEODOGICA NEINEY  DOSWELL NEW MEXICO	TITLE		DATE	·	