

UNITED STATES DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO 88240SUBMIT INSTRUCTIONS  
(Other instructions on re-)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-032579-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

----

7. UNIT AGREEMENT NAME

----

8. FARM OR LEASE NAME

Union Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Langlie Maddix-7R,Q,Gb

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 27, T25S, R37E

12. COUNTY OR PARISH

Lea

13. STATE

N. M.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Morris R. Antweil

3. ADDRESS OF OPERATOR

Box 2010, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1980' FNL and 330' FEL of Section 27

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3031.4 GR

16.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐

PULL OR ALTER CASING

☐  
☐  
☐  
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐  
☐  
☐

REPAIRING WELL

☐  
☐  
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) Cement Csg. &amp; Test

☒(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spud well 26 Dec., 1981. Drill 12-1/4" hole to 376'. Run 8-5/8" 24# H-40 Casing and Cement at 376' with 250 sacks Class C Cement with 2% CaCl<sub>2</sub>. Circulated Cement. Plug down 9:30 PM 26 Dec., 1981. WOC 12 hrs. Test Casing, 800 psi-30mins-OK. Drill out with 7-7/8" bit.

DEC 30 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*[Signature]*

TITLE

Agent

DATE

29 Dec., 1981

(This space for Federal or State office use)

ACCEPTED FOR RECORD  
ROGER A. CHAPMAN

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side