

2. SER. 1500 HAM-TYPE DOP (8)

3. 3" SER. 1500 VALVE

4. SER. 1500 DRILLING SPOOL

5. 3" SER. 1500 X 2" SER. 1500 STEEL TEE

6. 2" SER. 1500 VALVE

7. 2" MUD PRESSURE GAUGE

8. 3" SER. 1500 X 2" SER. 1500 STEEL CROSS

9. 2" SER. 1500 ADJ. CHOKE

10. 2" SER. 1500 ADJ. CHOKE ON 2" SER. 1500 RISER VALVE ON SIDE OUTLET OF 2" SER. 1500 STEEL TEE

11. ADAPTER, 2" SER. 1500 X 10,000 LB FLANGE MATING 13 INLET

12. 10,000 LB WP REMOTE CHOKE

13. HYDRAULIC CHOKE, 2500 LB WP OR BETTER

14. 3" SER. 1500 CHECK VALVE

5000 PSI WP OR BETTER CLAMP BUNS MAY BE SUBSTITUTED FOR FLANGES

ONE ADJUSTABLE CHOKE MAY BE REPLACED WITH A POSITIVE CHOKE

VALVES MAY BE EITHER HAND OR POWER OPERATED BUT, IF POWER OPERATED, THE VALVES FLANGED TO THE DOP MUST BE CAPABLE OF BEING OPENED AND CLOSED MANUALLY OR CLOSE ON POWER FAILURE AND BE CAPABLE OF BEING OPENED MANUALLY

5000 PSI WORKING PRESSURE
BLOWOUT PREVENTER LOOK-UP
(SERIES 1500 FLANGES OR BETTER)

NOTES

1. 5000 PSI WP OR BETTER CLAMP BUNS MAY BE SUBSTITUTED FOR FLANGES
2. ONE ADJUSTABLE CHOKE MAY BE REPLACED WITH A POSITIVE CHOKE
3. VALVES MAY BE EITHER HAND OR POWER OPERATED BUT, IF POWER OPERATED, THE VALVES FLANGED TO THE DOP MUST BE CAPABLE OF BEING OPENED AND CLOSED MANUALLY OR CLOSE ON POWER FAILURE AND BE CAPABLE OF BEING OPENED MANUALLY

