Box 1973 HUBBS. NEW MEXICQ ESCAD Budget Bulkaw Mo. 42 B134 DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY Imaget Bulkaw Mo. 42 B134 SUNDRY NOTICES AND REPORTS ON WELLS Imaget Bulkaw Mo. 42 B134 SUNDRY NOTICES AND REPORTS ON WELLS Imaget Bulkaw Mo. 42 B134 1. odi well exact born born programme in the formation of the bulk of t	Form 9331	P. O. DOV. 1995 Form Approved.				
DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS Chemotowich for my proceeded and the and different of phage back to a different of the form of the for	Dec. 1973	HOBBS, NEW	MEXICA OOTA	Budget Bu	ireau No. 42-	R1424
GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS Colspan="2">Colspan="2" Colspan="2"		UNITED STATES	5. LERSE 40			-
SUNDRY NOTICES AND REPORTS ON WELLS 7. UNIT AGREEMENT NAME Device us the form as concents to entil or determ or plug back to a different 6. FAIM OR LEASE NAME 1. different concents to entil or determ or plug back to a different 8. FAIM OR LEASE NAME 2. NAME OF OPERATOR			NM-14167	· 1	<u> </u>	
BUTCHT NOTICES AND INCOMPLETED OF AND INCLOSED 1. officeness of the second s		GEOLOGICAL SURVEY	6. IF INDIAN,	ALLOTTEE OR	TRIBE NAM	IE
BUTCHT NOTICES AND INCOMPLETED OF AND INCLOSED 1. officeness of the second s				EMENIT NAME	•	-
1 output get					•	
weil L weil L other 2. NAME OF OPERATOR 9. WH1 M3 Robert N. Enfield 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR Wildcat NAME 9.0. Box 2431, Santa Fe, NM 87501 11. Sec. T, R. M., OR BIK AND SURVEY OR ARTA 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 15. ECC. T, R. M., OR BIK AND SURVEY OR ARTA AT TOP PROD. MTERME & 1980' FWL of Sec. 15 11. Sec. T, R. M., OR BIK AND SURVEY OR ARTA AT TOP PROD. MTERME BOX TO INDICATE NATURE OF NOTICE, REPORT OF 15. ELEVATIONS (SHOW DF, KDB, AND WD) REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF FRACTURE TERAT 10. HELL OR WILDEAT SHUTOFF SHOOT OR ACIDIZE 11. ELEVATIONS (SHOW DF, KDB, AND WD) JULT PLE COMPLETE 11. ELEVATIONS (SHOW DF, KDB, AND WD) YOLL OR ALTER CASING 11. ELEVATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally diffice give subsurface locations and May 29, 1982 - Drilled to a depth of 660' May 30, 1982 - Drilled to a depth of 2080' - 1/2°, 2943' - 3/4° June 1, 1982 - Drilled to a depth of 2080' - 1/2°, 2943' - 3/4° June 2, 1982 - Drilled to a depth of 3685' - anhydrite Deviation survey at 3670' - 1/2° June 2, 1982 - Set plug at 1360' w/75 sx	reservo.r. Use Fo	form for proposals to drill or to deepen or plug back to a difference or 9–331C for such proposals.)	8. FARM OR L	EASE NAME		*** * ;
wind L. wein C. Wein C. Uniter Uniter Robert N. Enfield	1. oil	gas	Federal	יזבו	<u></u>	1
Robert N. Enfield 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR 10. FIELD OR WILDCAT NAME 9.0. BOX 2431, Santa Fe, NM 87501 11. Stc. T. R. M. OR BLK. AND SURVEY OR AREA 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 NEA AT TOP PROD'NIE MENDE & 1980' FWL of Sec. 15 12. SCOUNTY OR FARST 33. STATE AT TOP APPROPHIE 800' FWL of Sec. 15 AT TOP APPROPHIE 800 TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA SUBSEQUENT REPORT OF: 16. CHECK APPROPHALTOS SUBSEQUENT REPORT OF: TEST WATER SHU-OFF 11. Stc. T. R. M. OR BLK. AND WD) REPAIR WELL 11. Stc. T. R. M. OR DF. KOB, AND WD) SHOOT OR ACIDIZE 11. Stc. T. R. M. OR DF. KOB, AND WD) REPAIR WELL 11. Stc. T. R. M. OR DF. KOB, AND WD) SHOOT OR ACIDIZE 11. Stc. T. R. M. OR DF. KOB, AND WD) REPAIR WELL 11. Stc. T. R. M. OR DF. KOB, AND WD) SHOOT OR ACIDIZE 11. Stc. T. R. M. OR DF. KOB, AND WD) SHOOT OR ACIDIZE 11. Stc. T. R. M. OR DF. KOB, AND WD) SHOOT OR ACIDIZE 11. Stc. T. M. M. Stc. SHOW DF. KOB, AND WD) SHOOT OR ACIDIZE 11. Stc. T. R. M. OR DF. KOB, AND WD) SHOR ORPELT NE TOR DF. T. M. STORE AND MAREA		<u> </u>	9. WELL NO.			-
3. ADDRESS OF OPERATOR P.O., Box 2431, Santa Fe, NM 87501 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 biow.) AT SURFACE: 360', F.M. & 1980', F.W. of Sec. 15 AT TOP FROD. 70 FILE (ML & 1980', F.W. of Sec. 15 AT TOP FROD. 70 FILE (ML & 1980', F.W. of Sec. 15 AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA. REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: FRACTURE TREAT OPUL OR ALTER CASING MULTPLE COMPLETE OHANGE SONES MAY 29, 1982 - DTITLED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and the writed detypts of 7400' - 1/2° JUNE 1, 1982 - DTITLED to a depth of 6280' - anhydrite Deviation survey at 2450' - 1/2° June 1, 1982 - DTITLEd to a depth of 3572' - anhydrite Deviation survey at 3462' - 1/2° June 2, 1982 - DTITLEd to a depth of 3570' - 1/2° June 3, 1982 - DTITLE dto a depth of 3570' - 1/2° June 3, 1982 - Set plug at 360' w/27 sx Set plug at 560' w/27 sx						<u> </u>
P.O. Box 2431, Santa Fe, NM 87501 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) AT SURFACE: 360' FML & 1980' FWL of Sec. 15 AT TOP ROD. MIERKAL: & 1980' FWL of Sec. 15 AT TOP ROD. MIERKAL: & 1980' FWL of Sec. 15 AT TOP ROD. MIERKAL: & 1980' FWL of Sec. 15 AT TOP APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUTOFF FRACTURE TREAT SHOOT OR ACIDIZE HANGE ZONES ABANDON* (ether) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give per						
A. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) AT TOP PROD. "MERLINE & 1980' FWL of Sec. 15 AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA. REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TST WATER SHUTOFF FRACTURE TREAT HULL OR ALTER CASING WULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all partiment details, and give pertiment dates, including setimated date of starting any proposed work. If well is disclinably diffield, give subsurface locations and measured and true vertical depths for all markers and zones pertiment to this work.)* May 29, 1982 – Drilled to a depth of 660' May 30, 1982 – Drilled to a depth of 660' May 31, 1982 – Drilled to a depth of 3685' – anhydrite Deviation survey at 3452' – 1/2° June 1, 1982 – Drilled to a depth of 3685' – anhydrite Degrad well, loggers TD 3678' Deviation survey at 3452' – 1/2° June 3, 1982 – Set plug at 300' w/78 sx Set plug at 560' w/27 sx Released rig at 1 AM 6/3/82 Subsurface Safety Valve: Manu, and Type I8. Incelow performer former state office use) APPROVED BY APPROVED TTHE COMPLETED CHERATIONS on Reverse Side APPROVED BY APPROVED TTHE COMPLETED OPERATIONS (Clearly state all partiment details, and give pertiment dates, including set starting any proposed owner, if well is disclosed with a state office use) APPROVED ST Subsurface Safety Valve: Manu, and Type I8. Incelow performer were stated office use) APPROVED BY APPROVED THE COMPLETED OPERATIONS on Reverse Side APPROVED BY APPROVED BY APPROVED THE Set @ PROVED THE CONDITIONS BY APPROVED THE APPROVED BY APPROVED BY APPROVED BY APPROVED BY APPROVED ST CONDITIONS BY APPROVED THE Set mature State office use) APPROVED BY APPROVED BY A				MORBIK	AND SURV	
below) AT SURFACE: 3G0 + ENL & 1980' FWL of Sec. 15 AT TOP PROD. WHEREAL & 1980' FWL of Sec. 15 AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT:OFF FRACTURE TREAT SHOOT OR ACIDIZE REPART. WELL OULT OR ALTER CASING WULTIPLE COMPLETE OHARG ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give subsurface locations and measured and true vertical depth of 2080' - 1/2°, 2943' - 3/4° June 1, 1982 - Drilled to a depth of 3672' - anhydrite Deviation survey at 3670' - 1/2° June 2, 1982 - Drilled to a depth of 3685' - anhydrite Deviation survey at 3670' - 1/2° June	4. LOCATION	OF WELL (REPORT LOCATION CLEARLY, See space 1				· ·
AT TOP PROC. "MITERVAL'S of 1950 THE OF SEC. 13 AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF PULL OR ALTER CASING PULL OR ALTER CASING PULL OR ALTER CASING PULL OR ALTER CASING WULTIPLE COMPLETE CHANGE ZONES ABANDON' (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent deta ABANDON' (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent deta May 29, 1982 - Drilled to a depth of 660' May 30, 1982 - Drilled to a depth of 3232' - anhydrite Deviation survey at 2450' - 1/2°, 2943' - 3/4° June 1, 1982 - Drilled to a depth of 3685' - anhydrite Deviation survey at 3462' - 1/2° June 2, 1982 - Drilled to a depth of 3685' - anhydrite Deviation survey at 3460' - 1/2° June 3, 1982 - Set plug at 1360' w/27 sx Released rig at 1 AM 6/3/82 Subsurface Safety Valve: Manu. and Type 18. Therefy valve: Manu. and Type Robert N. Entield COMPLETED OF Relator THE NOV 2 1982 PROVED THE NOV 2 1982 PROVED THE Steep PROVED THE NOV 2 1982 PROVED THE Steep PROVED THE PROVED THE						•
AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3121.5 GR 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3121.5 GR 16. CHECK APPROPAL TO: SUBSEQUENT REPORT OF: 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent details, including estimated date of stating any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for dates of stating any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for 3222' - anhydrite Deviation survey at 2450' - 1/2°, 2943' - 3/4° June 1, 1982 - Drilled to a depth of 3652' - anhydrite Deviation survey at 3620' - 1/2° June 2, 1982 - Drilled to a depth of 3652' - anhydrite Deviation survey at 3620' - 1/2° June 3, 1982 - Set plug at 1360' w/50 sx Set plug at 1360' m/27 sx Released rig at 1 AM 6/3/82 Subsurface Safety Valve: Manu. and Type ROPER N. EntileID chas gave for Foderal or State affice use APPROVED W NOV 2 1962 FOR JANES A. GILHAAN *See Instructions on Reverse Side	AT SURF	ACE: 360'_ENL & 1980' FWL of Sec. 15	12. COUNTY OF	A PARISH 13	STATE	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 3121.5 GR TEST WATER SHUT-OFF FRACTURE TREAT 10. PULL OR ACIDIZE REPAIR WELL (NOTE: Report results of multiple completion or zone Change on Form 9-330.) 10. 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 16. May 29, 1982 - Drilled to a depth of 2080' - anhydrite Deviation survey at 2450' - 1/2°, 2943' - 3/4° 3/4° June 1, 1982 - Drilled to a depth of 3635' - anhydrite logged well, loggers TD 3678' Deviation survey at 3670' - 1/2°, 2943' - 3/4° 10. June 2, 1982 - Drilled to a depth of 3658' - anhydrite logged well, loggers TD 3678' Deviation survey at 3670' - 1/2° 10. June 3, 1982 - Set plug at 3300' w/78 sx Set plug at 360' w/75 sx Released rig at 1 AM 6/3/82 13. Subsurface Safety Valve: Manu. and Type APPROVED BY Set @ Ft. 18. Thereby certity bother foreologies in true and correct storte. MOY 2 1982 THE APPROVED W APPROVED APPROVED BY DATE DATE APPROVED W APPROVED APPROVED BY DATE <						<u> </u>
REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 3121.5 GR TEST WATER SHUT-OFF Image on Form 9-330.1 Image on Form 9-330.1 REPAIR WELL Image on Form 9-330.1 Image on Form 9-330.1 PULL OR ALTER CASING Image on Form 9-330.1 Image on Form 9-330.1 MULTIPLE COMPLETE Image on Form 9-330.1 Image on Form 9-330.1 IT. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* May 20, 1982 - Drilled to a depth of 2080' - anhydrite Deviation survey at 2450' - 1/2°, 2943' - 3/4° June 1, 1982 - Drilled to a depth of 3678' Imarkers 1120° June 2, 1982 - Drilled to a depth of 3678' Imarkers 1120° June 3, 1982 - Set plug at 3300' w/78 sx Set plug at 1360' w/50 sx Set plug at 560' w/75 sx Set plug at 560' w/75 sx Subsurface Safety Valve: Manu. and Type Set @@ FF Is. Ihereby certify first he foregoing is true and correct Set @@ FF Subsurface Safety Valve: Manu. and Type DATE APPROVED BY APPROVED THE </td <td></td> <td></td> <td></td> <td></td> <td>고 정철문</td> <td></td>					고 정철문	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 3121.5 GR TEST WATER SHUT-OFF					<u> </u>	
TEST WATER SHUT-OFF Image: Constraints of multiple completion or zone change on form 9-330. REFAIR WELL Image: Constraints of multiple completion or zone change on form 9-330. MULTPLE COMPLETE Image: Constraints of multiple completion or zone change on form 9-330. MULTPLE COMPLETE Image: Constraints of multiple completion or zone change on form 9-330. MULTPLE COMPLETE Image: Constraints of multiple completion or zone change on form 9-330. MULTPLE COMPLETE Image: Constraints of multiple completion or zone change on form 9-330. MULTPLE COMPLETE Image: Constraints of multiple completion or zone change on form 9-330. MULTPLE COMPLETE Image: Constraints of multiple completion or zone change on form 9-330. MULTPLE COMPLETE Image: Constraints of multiple completion or zone change on form 9-330. May 29, 1982 - Drilled to a depth of 2080' - anhydrite Image: Constraints of multiple completion or zone of 2322' - anhydrite May 31, 1982 - Drilled to a depth of 3572' - anhydrite Deviation survey at 3670' - 1/2° June 1, 1982 - Drilled to a depth of 3678' anhydrite Deviation survey at 3300' w/78 sx Set plug at 360' w/27 sx Set plug at 560' w/27 sx Released rig at 1 AM 6/3/82 Subsurface Safety Valve: Manu. and Type Date MOV APPROVED	REFORT, OR OTHER DATA		15. ELEVATION	S (SHOW DF,	, KDB, ANI	ວັWD) -
FRACTURE TREAT Image: Complete the second secon	REQUEST FOR	APPROVAL TO: SUBSEQUENT REPORT OF:	<u></u>		<u></u>	
SHOOT OR ACIDIZE Image: Shoot of a construction of a con	TEST WATER	SHUT OFF				
REFAR WELL (NOTE: Report results of multiple completion or zone change on Form 9-330.) PULL OR ALTER CASING (NOTE: Report results of multiple completion or zone change on Form 9-330.) MULTIPLE COMPLETE (NOTE: Report results of multiple completion or zone change on Form 9-330.) II. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* May 29, 1982 - Drilled to a depth of 2080' - anhydrite Deviation survey at 2450' - 1/2°, 2943' - 3/4° June 1, 1982 - Drilled to a depth of 3685' - anhydrite Deviation survey at 3462' - 1/2° June 2, 1982 - Drilled to a depth of 3685' - anhydrite Deviation survey at 3670' - 1/2° June 3, 1982 - Set plug at 3300' w/78 sx Set plug at 160' w/27 sx Released rig at 1 AM 6/3/82 Subsurface Safety Valve: Manu. and Type I8. Ihereby certify that the foreoing is true and correct signed Signed MOY 2 1962 NOY 2 1962			2			-
PULL OR ALTER CASING Implementation of the change on Permission form 9-330.) MULTIPLE COMPLETE Implementation of the change on Permission form 9-330.) CHANGE ZONES Implementation of the change on Permission form 9-330.) I7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* May 29, 1982 - Drilled to a depth of 2080' - anhydrite May 30, 1982 - Drilled to a depth of 3232' - anhydrite Deviation survey at 2450' - 1/2°, 2943' - 3/4° June 1, 1982 - Drilled to a depth of 3685' - anhydrite logged well, loggers TD 3678' Deviation survey at 3670' - 1/2° June 3, 1982 - Set plug at 3300' w/78 sx Set plug at 560' w/27 sx Released rig at 1 AM 6/3/82 Subsurface Safety Valve: Manu. and Type Robert IN, EnfleId This space for Federal or State office use) APPROVED APPROVED NOV 2 1982 NOV 2 1982 For NOV 2 1982 For NOV 2 1982 For APPROVED			(NOTE: Report re	culte of multiple		÷.
CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* May 29, 1982 - Drilled to a depth of 660' May 30, 1982 - Drilled to a depth of 3232' - anhydrite Deviation survey at 2450' - 1/2°, 2943' - 3/4° June 1, 1982 - Drilled to a depth of 3572' - anhydrite Deviation survey at 3462' - 1/2° June 2, 1982 - Drilled to a depth of 3685' - anhydrite Deviation survey at 3462' - 1/2° June 3, 1982 - Set plug at 3300' w/78 sx Set plug at 1360' w/50 sx Set plug at 1360' w/50 sx Set plug at 560' w/27 sx Released rig at 1 AM 6/3/82 Subsurface Safety Valve: Manu. and Type 18. Thereby certify fighthe threefoing is true and correct sioned MOV 2: 1982 NOV 2: 1982 PROVED NOV 2: 1982 NOV 2: 1982 PROVED NOV 2: 1982 NOV 2: 1982 PROVED NOV 2: 1982 PROVED PRO						Sr zone
ABANDON* L L (other) II DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* May 29, 1982 - Drilled to a depth of 660' May 30, 1982 - Drilled to a depth of 3232' - anhydrite Deviation survey at 2450' - 1/2°, 2943' - 3/4° June 1, 1982 - Drilled to a depth of 3672' - anhydrite Deviation survey at 3462' - 1/2° June 2, 1982 - Drilled to a depth of 3678' - anhydrite Dogged well, loggers TD 3678' Deviation survey at 3670' - 1/2° June 3, 1982 - Set plug at 3300' w/78 sx Set plug at 360' w/50 sx Set plug at 360' w/27 sx Released rig at 1 AM 6/3/82 Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foreologies is true and correct Sioned APPROVED ROPEr N. EntiteId Chis space for Federal or State office use) APPROVED The NOV 2 1982 Date INOV 2 1982 The OR APPROVED NOV 2 1982 TOR See Instruc						
(other) Implicit and the proposed of a string any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* May 29, 1982 - Drilled to a depth of 2080' - anhydrite May 30, 1982 - Drilled to a depth of 322' - anhydrite Deviation survey at 2450' - 1/2°, 2943' - 3/4°. June 1, 1982 - Drilled to a depth of 3572' - anhydrite Deviation survey at 2450' - 1/2°. June 2, 1982 - Drilled to a depth of 3655' - anhydrite Deviation survey at 3462' - 1/2°. June 2, 1982 - Drilled to a depth of 3678' Deviation survey at 3670' - 1/2°. June 3, 1982 - Set plug at 3300' w/78 sx Set plug at 560' w/27 sx Released rig at 1 AM 6/3/82 Subsurface Safety Valve: Manu. and Type 18. I hereby certify fract the foreologies is true and correct store' May 4 PPROVED Robert N. EntiteId CONDITIONS OF APPROVED NOV 2 1982 Ft. APPROVED NOVED NOV 2 1982 For APPROVED The APPROVED The Darte CONDITIONS of APPROVAL & ANY. CONDITIONS of APPROVED The Darte CONDITIONS of APPROVAL & ANY. CONDITIONS of APPROVED <td></td> <td></td> <td>~</td> <td></td> <td>김 문화님</td> <td>8 문 전</td>			~		김 문화님	8 문 전
<pre>including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* May 29, 1982 - Drilled to a depth of 660' May 30, 1982 - Drilled to a depth of 2080' - anhydrite Deviation survey at 2450' - 1/2°, 2943' - 3/4° June 1, 1982 - Drilled to a depth of 3572' - anhydrite Deviation survey at 3462' - 1/2° June 2, 1982 - Drilled to a depth of 3685' - anhydrite Degreation survey at 3670' - 1/2° June 3, 1982 - Set plug at 3300' w/78 sx Set plug at 1360' w/50 sx Set plug at 160' w/50 sx Released rig at 1 AM 6/3/82 Subsurface Safety Valve: Manu. and Type Robert N. Entield Conditions of rederal or State office use) APPROVED BY APPROVED THE CONDITIONS of APPROVED IAMES A. GILLHAAN *See Instructions on Reverse Side IAMES A. GILLHAAN *See Instructions on Reverse Side</pre>				n and a second s		
CONDITIONS OF APPROVAL LE ANVI. CHES (20) NOV 2 1982 FOR *See Instructions on Reverse Side	including measured May 29, May 30, May 31, June 1, June 2, June 2, June 3, 1 Subsurface Sa 18. Thereby co SIGNED RODE	estimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertir 1982 - Drilled to a depth of 660' 1982 - Drilled to a depth of 2080' - 1982 - Drilled to a depth of 3232' - Deviation survey at 2450' - 1/ 1982 - Drilled to a depth of 3572' - Deviation survey at 3462' - 1/ 1982 - Drilled to a depth of 3685' - 10gged well, loggers TD 3678' Deviation survey at 3670' - 1/ 982 - Set plug at 3300' w/78 sx Set plug at 1360' w/50 sx Set plug at 560' w/27 sx Released rig at 1 AM 6/3/82 fety Valve: Manu. and Type ertify that the foregoing is true and correct TITLE Deriator TITLE Deriator	anhydrite anhydrite anhydrite (2°, 2943' - 3 anhydrite (2° anhydrite 2° anhydrite 2° bATE 672 office use)	give subsurf	ace location between the second secon	LS and
FOR See Instructions on Reverse Side		APPROVAL LE ANY. CHESCER			(N)	
JAMES A. GILHAM						:
	-	JAMES A. GILHAN	e Side			

: