

UNITED STATES HOBBS, NEW MEXICO 88240

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR
TEXACO INC.

3. ADDRESS OF OPERATOR
P.O. Box 728, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
455' FNL & 1980' FWL
AT SURFACE: (Unit Letter 'C')
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other)			

5. LEASE
LC-062300

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
-

7. UNIT AGREEMENT NAME
-

8. FARM OR LEASE NAME
Cotton Draw Unit

9. WELL NO.
75

10. FIELD OR WILDCAT NAME
Paduca Delaware

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 15, T-25-S, R-32-E

12. COUNTY OR PARISH
Lea

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3447' (GR)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

SEP 13 1982

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TOTAL DEPTH 4750'

8 5/8" OD 24# J-55 CSG SET @ 355'

1. Ran 4739' (119 Jts.) 5 1/2" OD 15.5# K-55 Csg & set @ 4750'.
2. Cement 1st stage W/500 Sx. LW Cement containing 15# salt & 1/4# flocele per sack followed W/200 sx. Class 'H' Cement containing 8# salt & 1/4# flocele per sack.
3. With DV tool open @ 1165', cemented 2nd stage W/400 sx. Class 'H' Cement containing 2% CaCl. Cement circulated. Job complete 10:30 AM, 9-2-82. WOC in excess of 18 Hrs.
4. Tested 5 1/2" csg to 1500# for 30 minutes, 11:00-11:30 AM, 9-9-82. Tested OK. Job complete 11:30 AM, 9-9-82.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Asst. Dist. Mgr. DATE 9-10-82

(ORIG. SGD.) DAVID R. GLASS
(This space for Federal or State office use)
APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL ANY 8 1982U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side