	*	New N	Aexico (NI C-15ervell	
		~	-	164. J. Frenz	
			AND	Hobbs, NM	Some of
Form 3160-5	UNITED				FORM APPROVED
(August 1999)	DEPARTMENT O				MB NO. 1004-0135
(1 original, 5 copies)	BUREAU OF LAN SUNDRY NOTICES AND				es: November 30, 2000
Do	not use this form for propo			5 Lease Serial N NM NM 9	
	ndoned well. Use Form 316				tee or Tribe Name
	IN TRIPLICATE - Other ins			=	
002				7 If Unit or CA/A	greement, Name and/or No.
1. Type of well					
X Oil Well G	as Well Other	·····		Red Hills North 8 Well Name and	
EOG Resources, Inc.				8 Well Name and Red Hills North	
Ba. Address P.O. Box 2267, Midland, TX		o. (include area code)		9 API Well No. 30-025-28003	
4. Location of Well (Foota	age, Sec., T.,R.,M., or Survey Des			10 Field and Pool	, or Exploratory
<i>1978</i> 1980' ENL & 1980' EEL Sec	tion 17, T-25-S, R-34-E (S/L)	÷		Red Hills Bone	
	n 17, T-25-E, R-34-E (BHL)			Lea Co. NM	isn, State
	ICE, REPORT, OR OTHER DATA				
YPE OF SUBMISSION					
	Acidize	Deepen		luction (Start/Resume)	Water Shut-Off
XI Notice of Intent	Alter Casing	Fracture Treat		amation	Well Integrity
Subsequent Report	Change Plans	New Construction	2344022	omplete porarily Abandon	LX Other
Final Abandonment N				poraniy Abandon er Disposal	Recomplete Horizontally
If the proposal is to deeper	pleted Operation (clearly state all pertine or directionally or recomplete horizontally, the work will be performed or provide to	CIVE SUBSUITACE locations and mo-	seurad and tru	a varical dapths of all pa	tipopt modeum and same
tollowing completion of the	involved operations. If the operation res Final Abandonment Notices shall be fil	ults in a multiple completion or recu	ompletion in a	new interval a Form 3160	A shall be filed on:
determined that the site is re	ady for final inspection.	ed only alter all requirements, inca	uoing reciamai	ion, nave been completed	
Attached he	ere to Drilling Program, Surface use	and Operations Plan for Horizo	ontal re-entry	of producing well	LIKE APPRO
Bond No. or C-102 Plats	n file with BLM NM2308			, , , , , , , , , , , , , , , , , , ,	
0+102 Flats	enciosed.	APPROVE	D I		BY STATE
		DEC 26			
		GARY GOURLEY			
		PETROLEUM ENGINE	ER		
 I hereby certify that the f Name (Printed/Typed) 	oregoing is true and correct		1		
Mike Francis	<u> </u>		Title		Agent
gnature	7		Date		12/20/01
DERAL OR STATE OFFIC	CAMere				
	·····			1	
pproved by				Title	Date
	, are attached. Approval of this not	ce does not warrant or			
onditions of approval, if any	, are attached. Approval of this not s legal or equitable title to those righ			Office	

States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

5 C S

Ke

trict Office - 4 Copies - 3 Copies REPORT
mber
1
ion
LEA
LEA
LIDATED
···· ·································
ATION I herein is to and belief.
n this plat made by me true and 1

EOG RESOURCES, INC. RED HILLS NORTH UNIT NO. 901 LEA COUNTY, NM

1. <u>GEOLOGIC NAME OF SURFACE FORMATION</u>: Permian

2. ESTIMATED TOPS OF IMPORTANT GEOLOGICAL MARKERS:

Delaware Mt. Group	5320'
Bone Spring Lime	9305'
3 rd Bone Spring Sand	12250'
TVD	12350'
TMD	15550'

3. ESTIMATED DEPTHS OF ANTICIPATED FRESH WATER, OIL OR GAS:

Upper Permian Sands	100'	Fresh Water
3 rd Bone Spring Sand	12250'	Oil

No other formations are expected to give up oil, gas or fresh water in measurable quantities. The surface fresh water sands are protected by setting 13 3/8" casing at 588' and cement circulated back to surface.

4. CASING PROGRAM: (Existing Casing)

Hole Size	Interval	OD Casing	Weight Grade Jt. Cond. Type
17 1/2"	0-588'	13 3/8"	54.5# J55 ST&C
12 1/4"	0-5172'	10 3/4"	45.5# LT&C
9 1/2"	8757-13,600'	7 5/8"	33.7, LT&C
7 7/8"	0'-12,170'	5 1/2"	17# TAC95 & P-110
7 7/8 ''	13099-15820'	5 1⁄2" LINER	17# P-110

CASING PROGRAM : (Proposed)

<u>Hole Size</u>	Interval	OD Casing	Weight Grade Jt. Cond. Type
4 ¾"	11,700-15550'		9.2 HCP-110, HYD 513

CEMENTING PROGRAM: (Existing Casing)

13 3/8" Surface Casing: Circulated cement to surface w/500 Sx.

10 3/4" 1st Intermediate: Circulated cement to surface w/2825 Sx.

EOG RESOURCES, INC. RED HILLS NORTH UNIT NO. 901 LEA COUNTY, NM

- 7 5/8" 2nd Intermediate: Cemented with 795 sx. TOC @ 8757'
- 5 1/2" Production Casing: Cemented with 85 sx. Premium Plus. TOC @ 11090' by Temperature log.

5 ¹/₂" Liner: NR

CEMENTING PROGRAM: (Proposed)

3 1/2" Production Liner: 160 sxs Acid Soluble Cement, 0.6%Halad344,0.7%Econolite,0.2% SCR-100

5. <u>Re-ENTRY PROCEDURE:</u>

The RHNU #901 well will be re-entered. The existing perforations are in the Third Bone Springs @ 12,264' - 12,290'. A 5 $\frac{1}{2}$ CIBP will be set @ 12,150' and 35' of cement placed on top.

A 5 $\frac{1}{2}$ mechanical whipstock will be set @11,700', window cut, and a 4 $\frac{3}{4}$ " hole drilled horizontally to approximately 15,550' MD. A 3 $\frac{1}{2}$ " production liner will be run and cemented in from 15,550 to 11,500'. See Exhibit 4(a), 4(b).

5. MINIMUM SPECIFICATIONS FOR PRESSURE CONTROL:

The blowout preventer equipment (BOP) shown in Exhibit #1 will consist of a double ram-type (5000 psi WP) preventer and an annular preventer (5000 psi WP). Units will be hydraulically operated and the ram-type will be equipped with blind rams on top and drill pipe rams on bottom. All will be installed on the 5 $\frac{1}{2}$ " production casing and used continuously until TD is reached. Before drilling out of the 5 $\frac{1}{2}$ " casing, the ram-type BOP and accessory equipment will be tested to 5000 psi and the annular to 70% of rated working pressure (3500 psi).

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. A 2" kill line and 4" choke line will be included in the drilling spool located below the ram-type BOP. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold with 5000 psi WP rating.

6. TYPES AND CHARACTERISTICS OF THE PROPOSED MUD SYSTEM:

EOG RESOURCES, INC. RED HILLS NORTH UNIT NO. 901 LEA COUNTY, NM

The well will be drilled to TD with a polymer/KCL mud system. The applicable depths and properties of this system are as follows:

<u>Depth</u>	Type	Wt (ppg)	Viscosity <u>(sec)</u>	Waterloss (cc)
11,700'to 15,550'	Fresh water/gel	8.33	28-40	N.C 10

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept at the wellsite at all times.

7. Auxillary Well Control and Monitoring Equipment:

(A) A kelly cock will be kept in the drill string at all times.

- (B) A full opening drill pipe stabbing valve (inside BOP) with proper drill pipe connections will be on the rig floor at all times.
- (C) A mud logging unit complete with H2S detector will be continuously monitoring drilling penetration rate and hydrocarbon shows.

8. LOGGING, TESTING AND CORING PROGRAM:

(A) The electric logging program will consist of a LWD GR from 11,700' to TD.

10. <u>ABNORMAL CONDITIONS, PRESSURES, TEMPERATURES AND</u> POTENTIAL HAZARDS:

No abnormal pressures or temperatures are anticipated. The estimated bottom hole temperature (BHT) at TD is 175 degrees F with an estimated maximum bottom-hole pressure (BHP) at TD of 5000 psig. No hydrogen sulfide or other hazardous gases or fluids have been encountered, reported or are known to exist at this depth in this area. No major loss circulation zones have been reported in offsetting wells.

11. ANTICIPATED STARTING DATE AND DURATION OF OPERATIONS:

Road and location work will not begin until approval has been received from the BLM. Anticipated spud date is within 30 days after approval at the present time. Once drilling has commenced, the drilling operation should be finished in approximately 60 days. If the well is productive, an additional 30 to 45 days will be required for the completion and testing before a decision is made to install permanent facilities.

EOG RESOURCES, INC. RED HILLS NORTH UNIT NO. 901 LEA COUNTY, NM

SURFACE USE AND OPERATIONS PLAN

1. EXISTING ROADS:

Access to location will be made on existing roads.

Routine grading and maintenance of existing roads will be conducted as necessary to maintain their condition as long as any operations continue on this lease.

2. LOCATION OF EXISTING WELLS:

Exhibit #2 shows all existing wells within a one-mile radius of this well.

3. LOCATION OF EXISTING AND/OR PROPOSED FACILITIES:

Existing production facilities and roads located within Red Hills North Unit (Exhibit 3) Flow lines are already in place for existing production.

4. LOCATION AND TYPE OF WATER SUPPLY:

Water for drilling will be purchased from commercial sources and transported to the well site over existing roads.

EOG RESOURCES, INC. RED HILLS NORTH UNIT NO. 901 LEA COUNTY, NM

5. PLANS FOR RESTORATION OF THE SURFACE:

After completion of drilling and/or completion operations, all equipment and other material not needed for operations will be removed. Location will be cleaned of all trash and junk to leave the well in an aesthetically pleasing condition as possible.

Any unguarded pits containing fluid will be fenced until they are dry and back filled.

After abandonment of the well, surface restoration will be in accordance with current federal laws and regulations. Location will be cleaned, and the well pad removed to promote vegetation. Reseeding will be as per BLM specifications

6. METHODS OF HANDLING WASTE DISPOSAL:

A small reserve pit will be utilized. Reserve pit will be evacuated of drilling fluid within 10 days after the well is completed.

Drill cuttings will be encapsulated in plastic and buried 2' below ground level.

Water produced during tests and waste water will be saved and hualed to a disposal well. Oil produced during tests will be in test tanks until sold.

Current laws and regulations pertaining to the disposal of human waste will be complied with.

Trash, waste paper, garbage and junk will be hauled to an approved disposal site n an enclosed trash trailer.

All trash and debris will be removed from the well site within 30 days after finishing drilling and/or completion operations.

7. ANCILLARY FACILITIES:

No airstrip, campsite, or other facilities will be built.

8. WELL SITE LAYOUT:

Exhibit #3 shows the relative location and dimensions of the well pad, steel mud pits, and location of major rig components. Pad area has been staked and flagged.

10. OTHER INFORMATION:

EOG RESOURCES, INC. RED HILLS NORTH UNIT NO. 901 LEA COUNTY, NM

The area around the well site is grassland and the top soil is duned and sandy. The vegetation is native scrub grasses with abundant sagebrush, yucca, and prickly pear.

There is no permanent or live water in the immediate area.

Cultural resources examination has been completed.

11. OPERATORS REPRESENTATIVE:

The field representative responsible for assuring compliance with the approved surface-use and operations plan is as follows:

Mr. Tom Young

Phone: Business 1/505/390/2903 Home 1/915/697-5639

EOG RESOURCES, INC. RED HILLS NORTH UNIT NO. 901 LEA COUNTY, NM

12. CERTIFICATION:

I HEREBY CERTIFY that I, or persons under my direct supervision, have inspected the proposed drill site and access route; that I am familiar with the conditions which presently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed by EOG Resources, Inc. and its contractors and sub-contractors in conformity with this plan and the terms and conditions under which it is approved.

12 7 Tom Young

Drilling Manager

Date: 12/20/01

EOG RESOURCES, INC. RED HILLS NORTH UNIT NO. 901 LEA COUNTY, NM

ATTACHMENT TO EXHIBIT #1

- 1. Blow out preventer and all fittings must be in good condition, 5000 psi W.P. minimum.
- 2. All fittings to be flanged.
- 3. Safety valve must be available on rig floor at all times with proper connections, valve to be full bore 5000 psi W.P. minimum.
- 4. All choke and fill lines to be securely anchored, especially ends of choke lines.
- 5. Equipment through which bit must pass shall be at least as large as the diameter of the casing being drilled through.
- 6. Kelly cock on kelly.
- 7. Extension wrenches and hand wheels to be properly installed.
- 8. Blow out preventer control to be located as close to driller's position as feasible.
- 9. Blow out preventer closing equipment to include minimum 40-gallon accumulator, two independent sources of pump power on each closing unit installation, and meet all API specifications.



	L.Beck U.S.M.I. U.S., MI etal M Diamond E. Half, Inc.(S)	K Diamond G. Half I.I. (nc. (S) Ri Modera, S	"Gov't" Billie Forther & Mary Hale	USMI. U.S., MI Billie Fortner SMary Hale 'ero, etal,	Shell-Fed 105511 State PASITE	Cella Gioschian (
son 066 1x0<0 138 P	Richardson Oil 2.1.61(1) 11 063798	Richardson 0il - endian 2-1.4 (2) -13-94 063798 -19-94 -19-94 -19-94 -19-94 -19-94	Superior HBP	hibit 2 isting wells	within one(1)	mile of
ieso Pet ockson U borr Dis 5 Mil 2 Dist. 13	23 Richard Son Oil	d. 24 Magarul R.E. 1. August R.E. 1. August 1. Condict 1. August 2:8-87	W/2 (0 101512)	oposed re-en	try r Re d Hills No	rth Unit
urchison 64 Texaco 6-5160	U. S., MI Diamond E. Haif, Inc. (S) U.S.	8. (<u>S.R. Mailionastal M.I.</u> Mabil U.S., MU H-13-84 (<u>11-9-94</u>) U.S. Rubert Marro	39.144 4 Yortes Pert. etal 4 , 5 : 1 · 39 V · 4372 27 21 Rub	198.2ac		
voj i Mil isse isse i HBC	So. Roy. H8P (HNG) 19858 Modered (Atoke Dsc.) 70(5)50 (125 Mich	(So.Roy, So.Roy, 6+1+54 1985 t 21308 Werddian Wg WZ	99 194 / Yates Pet. eta) 5 1 - 2001 87 49 87 49 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Enron Aztec 20061 inte * US.M.C.		
*SI. 3•64	26 (15 kild) 26 (15 kild) 27 (15 kild) 27 (15 kild) 28 (15 kild) 29 (15 kild) 29 (15 kild) 29 (15 kild) 29 (15 kild) 20	25 () () () () () () () () () () () () () (U.S. 50 Noverty	* Rubert Modera(S) 29 m Marshall-Fed.	U.S. M. Shi Fred J.A. Miss Me York Martin Martin J.C. Martin Martin J.C.	
ron 2000 4598 7599 ron	U.S. So Roy.	U.S. Sterie Enron	Store Loto Dillon, S Brite Enron	U.S. MI Diamond and Half Inc.	Contraction of the state of the	(200 - (Elisso) 2 Jamorra erra naj (R.C. Lanenth) 3
519 <u>562</u> ,	нер 1985е 35	10-+135 Kirkin 10-535 10-55 10	288st "Dillon"	зтоте 580 (А.4096) Могк А.4МИ. Disc (Анико) Елгоп HBC N/1 LG 359 32	HING) Plannond E Half State HING) Page	10 15455 (6130 marts) HBC W/2 (17057 (1900)
pak *		PR Dess Profession TD 5332 DA 5-Cal At 2404 TO 5,332 DA 5-Cal At 2404 TO 5,344		ORK 3 RANG	Will Horvey Jr. 33 4 1.9 Mil.	
21.5.5.1747-1	U.S. Henricht State - Biss an Ar states - Ar Henricht - Uniter- te base - Transition - States	1 Signe	Diomandia Half (S) Leve Dillion 33.34 August 33.34 August 2000 213246 / Enron 14437 6106 011	Starte (15 506) 168 / 21 2 15 338 / 4 (195 / 4) 3393 / 4) 44 / 05 / 4 (0) (200 / 62 / 164 / 0) Enrorn 500 / 640 / 62 / 164 / 0) (4 + 57 80 / 55 / Fed.) (4 + 57 80 / 55 / Fed.) (4 + 57 80 / 55 / Fed.) (5 + 56)	Access of the second se	
	2 Dinejf 6 8e// Lake (1. 4mii)	Guinozo, etal) 30400 T 5 aliwood fed F405) Enron Feder Taiteo Taiteo	of OJ 37Mil Tolster OJ 0J 37Mil Tolster Diamond Fred Enran English	Diamond 5-Fed		How Man Diamor
	VACA . Store	19859 3 F358 Hailwood-Fert 2 U.S. Filt	10 and 1 and	Enry Pilester U.S.	(Maridian) Antice Barrie Birlington Toisso "Prickfack Reh Red." U.S.	Otho Al Warren, M/. (U.S.
	CHankamer 1989 (Horan) Must of ad. 1989 (Horan) Must of ad. 1980 (Horan	FADO DEnran Birss (Quineco, stal) 30400 *rka * 6	1	torion Calling	Aztez • yean Heise • Starts	Harrison Perry Towner Strange, Jr. Margan Bryan Liss
^{блану} ф	Quinoco, etat BBP 30400	12 **** ********************************	Enrand 1733 1745 174	Enran Her Syn Enran Istag He Syn Jitta Enran Muse Syn	9	Acrys, p Acrys, p Acr
Iron	Exxon 8 - 27 - 95 95 322 Enron 95 322 HBP	Martin Strand State 1 500 Frs First State State 3 570 € U.S. Mr 570 € U.S. Mr 570 € U.S. Mr 6 000 5 5023 € 3 6 000 5 5023 € 5022 (Mr6GU) 5 5022 € 5022 5 502 € 502 € 502	2010 - Enron 3044 1 2 105 Enron 3 - 774 - 2044 1 2 105 Enron 3 - 774 - Enron	188 1944 1960 1853€ 19 19 1960 1965 195 195 195 195 195 195 195 195 195 19	Yotrs int, stal visits Visits int, stal visits	(0) Horaco, Diamonal & Hall Mitchell 13 - 1 - 5 204 92764
) / 197 / .		المعلم المعلم معلم المعلم المعلم المعلم المعلم المعلم المعلم المعلم المعلم المعلم المعلم المعلم المعلم	24480 24480 24480 2213 Digmond 213 Digmond 213 Digmond 24480 Digmond	Biomond Diamond Hills Million Half Indentified To Second Science of the Charles of the Harrison of the Harriso	16 Store	⁹² 2003 34
	MIDLAND © MAP	◆ Voco-Fed." 	Diamond Fed."	o ³	RCH.	U.S., MI EA Store, S
	Enron H8P 19623	Enron H8P 24490 24490	Ashmune Ashmune Hilliard Ne 5 Ltd	Erron 12005 3 1 2005 14425 94625 51099 51099	Enron 12.1/2004 94/03 179 22	Erron 12, 1, 2004 94100 48000
rÅ, etal 0-83	23	Amorco) Andrikopulóus Fed Marrow Dise: 24 IMIL Berria (Choco Sciencias)	Ashmuri E. Hilliard No.5 Ltd.	Holf 94109	2) Softwental Shift Malan Fed In 5603 MA 5603 States	U.S., M State, ! 22- Entron 12:1: 2004
, Dickeon	O DIA 10-26-62	Article Antonio Contraction and Antonio Contractiona antonio Contraction	67/mil/dur Fed 1 10/12609 plA/12:20-96 ⊕ U.S. NW4 ~1		U.S.	94110 4809: U.S.
87A 8-10-83	YatesPet,etai Texaco 3 39 9, - 2000 v.4318 VB 446 19 05 203 29 	12 1 2004 94101	Effort Chevron HBP 10 - 1 - 99 24490 V - 4481 Rafa 7 93 52	Chevron Enron 3 1 - 99 17 1 - 2004 Y 4320 94115 15 년 330 12	Enron 12 2004 94115 330 00	Enron 12 : I - 2004 94:10 480 99
H. Dick			nn i 30	29	28 Amoco /163500 (JA4-10-81	27
	la serie de la La serie de la s	**************************************	rifshell goge And a state of the state of th	Strine U.S.	DAA-ID-BI GOI-CG	<u></u>



۰.

EOG RESOURCES, INC. 1,980' FNL & 1,980' FEL Sec.17-T25S-R34E

RHNU NO. 901 LEA CO., NEW MEXICO DECEMBER 14, 2001

CURRENT WELLBORE SCHEMATIC



EOG RESOURCES, INC. 1,980' FNL & 1,980' FEL Sec.17-T25S-R34E

RHNU NO. 901 LEA CO., NEW MEXICO DECEMBER 14, 2001

PROPOSED WELLBORE SCHEMATIC

