

UNITED STATES OF AMERICA
NEW MEXICO 832405
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form G-331-C for such proposals.

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
The Stone Petroleum Corporation

3. ADDRESS OF OPERATOR
1110 N. Big Spring, Midland, TX 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980 FNL 1980 FNL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(check)

SUBSEQUENT REPORT OF:

6. IF INDIAN, ALLOTTEE OR INDIAN NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Javelina Basin Unit

9. WELL NO.

10. FIELD OR WILDCAT NAME
S. Pitchfork (Atoka)

11. SEC., T. R., M., OR BLK. AND SURVEY OR AREA
Sec. 17, T-25-S R-34-E

12. COUNTY OR PARISH 13. STATE
Lea New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3334.9 GR

(NOTE: Report results of multiple completion or zone change on Form G-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Attempt to establish injection into perfs @ 14594 - 14604. Unable to inject fluid at sufficient rate to pump cement - 7500 PSI.

Set CIBP @ 13,000' Spot 45SX cement on top

Spot 45SX cement @ 12,272' - 12,472'.

Spot 45 SX cement @ 11,522' - 11,722'.

Spot 45 SX cement @ 9,250' - 9,400'.

Cut 7 5/8" CSG @ 8819'. POH

Spot 50 SX cement @ 8,875'. Tagged TOC @ 8,720'

Spot 65 SX cement @ 6,176' Tagged TOC @ 6,020'

Spot 65 SX cement @ 5,400' - 5,250'

Spot 65 SX cement @ 3,600' - 3,500'

Spot 30 SX cement @ 1,450' - 1,550'

Spot 45 SX cement @ 550' - 650'

Spot 25 SX cement @ surf. Install marker. Clean Location

Subsurface Safety Valve: Manu. and Type Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

915-687-0323

SIGNED

Atoka

TITLE Agent

DATE 5-5-86

Orig. Sgd. Charles A. Dyer (This space for Federal or State office use)

APPROVED BY

Atoka

TITLE

DATE

8-8-86

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
JUN 14 1966
J.C.C.
HOBBS OFFICE