

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
The Stone Petroleum Corporation
3. ADDRESS OF OPERATOR
1620 Mid America Twr, Oklahoma City, OK
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 1980' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Run Casing

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

FEB 11 1983

OIL & GAS
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12 1/4" hole was drilled to 5172'. 118 joints of 10 3/4" S80 45.50# ST&C was set. Cemented with 2400 sxs pacesetter "lite" tailed in with 425 sxs class "C". Circulated 791 sxs to pit. WOC. Test casing to 1,000 psi 11/18/82.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Bradley T. Kasing TITLE Regional Drilling Manager DATE February 9, 1983

APPROVED BY (ORIG. SGD.) DAVID R. GLASS TITLE _____ DATE _____
CONDITIONS OF APPROVAL FEB 11 1983
MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO
See Instructions on Reverse Side