	TMENT OF THE INTERIOR	ONO DOMESTOCI	b. LEASE DESIGNATION AND S	
SUNDRY NC (Do not use this form for pro Use "APPL"	OTICES AND REPORTS BON  Possals to drill or to deepen of the back CATION FOR PERMIT—" HORSE STORES	19 <b>66</b> LLS 19 <b>66</b> LLS <b>W</b> MEXICO = 88240	NM 14497 6. IF INDIAN, ALLOTTEE OR T	RIBE NAME
OIL GAS X OTHER		7. UNIT AGREEMENT NAME		
2. NAME OF OPERATOR			8. FARM OR LEASE NAME	<del></del>
HNG OIL COMPANY			Diamond 5 Federal	L
3; ADDRESS OF OPERATOR	1 m 70702		9. WELL NO.	
P. O. Box 2267, Midland			1	
1. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)  At surface		10. FIELD AND POOL, OR WILDCAT Pitchfork Ranch Morrow		
660' FNL & 1980' FWL,	Center (NE NW) Sec. 5	•	Sec. 5, T25S, F	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT,	CR. etc.)	12. COUNTY OR PARISH 13.	
•	3410.8' GR		1	IM
16. Check A	Appropriate Box To Indicate Natur	re of Notice, Report, or (	Other Data	
NOTICE OF INT	ENTION TO:	SUBSEQ	UENT REPORT OF: 5/6/83	
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL,	
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING	
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	. ABANDONMENT*	
REPAIR WELL	CHANGE PLANS	(Other) Casing test	k cement joh. s of multiple completion on We	X
(Other)	PERATIONS (Clearly state all pertinent det	Completion or Recomp	detion Report and Log form.)	
nent to this work.) •	tionally drilled, give subsurface locations	and measured and true vertice	ul depths for all markers and a	ones pert
4-1/2" Liner set at	15,300'. P110, 13.50#.	TOP of liner at	13,012'. Cemented	with
4-1/2" Liner set at	15,300'. P110, 13.50#.	TOP of liner at	13,012'. Cemented	with
4-1/2" Liner set at	15,300'. P110, 13.50#.	TOP of liner at	13,012'. Cemented	with
4-1/2" Liner set at	15,300'. P110, 13.50#.	TOP of liner at	13,012'. Cemented	with
4-1/2" Liner set at	15,300'. P110, 13.50#.	TOP of liner at	13,012'. Cemented	with
4-1/2" Liner set at	15,300'. P110, 13.50#.	TOP of liner at increase the true vertex at increase the state of the	13,012'. Cemented  WOC - 32-1/4 ho	with
4-1/2" Liner set at	15,300'. P110, 13.50#.	TOP of liner at increase the true vertex at increase the state of the	13,012'. Cemented	with
4-1/2" Liner set at	15,300'. P110, 13.50#.	TOP of liner at increased to 2100	13,012'. Cemented  WOC - 32-1/4 ho	with
4-1/2" Liner set at	15,300'. P110, 13.50#.	TOP of liner at live tested to 2100	N 1 3 1983	with
4-1/2" Liner set at	15,300'. P110, 13.50#.	TOP of liner at live tested to 2100	13,012'. Cemented  WOC - 32-1/4 ho  N 1 3 1983	with
4-1/2" Liner set at	15,300'. P110, 13.50#.	TOP of liner at live tested to 2100	N 1 3 1983	with
4-1/2" Liner set at	15,300'. P110, 13.50#.	TOP of liner at live tested to 2100	N 1 3 1983	with
4-1/2" Liner set at 600 sacks Class H ce	15,300'. P110, 13.50#. ement. 30 minutes pressu	TOP of liner at live tested to 2100	N 1 3 1983	with
18. I hereby cartify that the foregoing SIGNED Betty Wildon	15,300'. P110, 13.50#. ement. 30 minutes pressu  is true and correct  Regul	TOP of liner at live tested to 2100	N 1 3 1983	with
4-1/2" Liner set at 600 sacks Class H ce	15,300'. P110, 13.50#. ement. 30 minutes pressu  is true and correct  Regul	TOP of liner at live tested to 2100	13,012'. Cemented  1. WOC - 32-1/4 ho  1. NEW MEXICO  6/10/83	with

ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side

RECEIVED

JUL 18 1983

HOBBS OFFICE