

N. M. OIL CONS. CO' ^{INCORPORATED}
P. O. BOX 1980
HOBBS, NEW MEXICO 88240UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. TYPE OF WORK

DRILL ☒DEEPEN ☐PLUG BACK ☐

b. TYPE OF WELL

OIL
WELL ☐GAS
WELL ☒OTHER ☐SINGLE
ZONE ☒MULTIPLE
ZONE ☐

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

21 Desta Drive, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)*

At surface

660' FNL & 1980' FWL, Sec. 4, T-25-S, R-34-E

At proposed prod. zone

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*

24 miles southwest of Jal, New Mexico

15. DISTANCE FROM PROPOSED*

LOCATION TO NEAREST
PROPERTY OR LEASE LINE, FT.
(Also to nearest drlg. unit line, if any)

660'

16. NO. OF ACRES IN LEASE

320

17. NO. OF ACRES ASSIGNED
TO THIS WELL

320

18. DISTANCE FROM PROPOSED LOCATION*
TO NEAREST WELL, DRILLING, COMPLETED,
OR APPLIED FOR, ON THIS LEASE, FT.

N.A.

19. PROPOSED DEPTH

15,400'

20. ROTARY OR CABLE TOOLS

Rotary

21. ELEVATIONS (Show whether DF, RT, GR, etc.)

3373' GR

22. APPROX. DATE WORK WILL START*

12-15-83

23.

PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
17 1/2"	13 3/8"	54.5#	600'	500 SX. CIRCULATE
12 1/4"	9 5/8"	36#	5250'	3500 SX. CIRCULATE
8 3/4"	7"	26#	13,250'	3000 SX.
6 1/8"	4 1/2"	15.10#	15,400'	500 SX.

Set 20" conductor @ 40'. Drl 17 1/2" hole & set 13 3/8" csg @ 600'. Circ cmt. Drl 12 1/4" hole & set 9 5/8" csg @ 5250'. Circ cmt. Drl 8 3/4" hole & set 7" csg @ 13,250'. Circ cmt up to 5250'. Drl 6 1/8" hole & set 4 1/2" liner from 12,950' to 15,400'. Complete in Morrow thru 2 7/8" tbg and PBR set in top of liner.

MUD PROGRAM: 0-600' spud mud; 600-5250' Brine water; 5250-13,250' cut Brine water; 13,250-15,400' invert oil base mud. MW 14.7#, VIS 60. BHP @ TD expected to be 10,000 psi.

BOP PROGRAM: 12"-3M annular BOP to be installed on 13 3/8" csg. 11"-10M BOP stack to be installed on 9 5/8" and left on for remainder of drilling. Stack to consist of drilling head, annular BOP, blind ram BOP, and two pipe ram BOP's. Test BOP's after setting 9 5/8" csg & 7" csg w/Yellow Jacket, Inc.

GAS NOT DEDICATED

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

SIGNED Danell Roberts TITLE Operations EngineerDATE 11-4-83

(This space for Federal or State office use)

PERMIT NO. _____

APPROVAL DATE _____

ORIG. SIGNED JAMES A. GILLHAM

ACTING

District Manager

APPROVED BY _____

TITLE _____

DATE 11-16-83

CONDITIONS OF APPROVAL, IF ANY: _____

*See Instructions On Reverse Side

APPROVAL SUBJECT TO
GENERAL REQUIREMENTS AND
SPECIAL STIPULATIONS
ATTACHED