P. O. BOX 1989 HOBBS, NEW MEXICO 88249

Form 9-331 Dec. 1973 Form Approved. Budget Bureau No. 42-R1424

UNITED STATES	5. LEASE	
DEPARTMENT OF THE INTERIOR	LC 054667	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME	
Testivon, de l'onn 3-001-0 to agui propositati	8. FARM OR LEASE NA	··· ·
1. o.i gas XXx other	El Paso Tom Federal	
WEII - WEII OTHER	9. WELL NO.	,
2. NAME OF OPERATOR	5	
Alpha Twenty-One Production Company	10. FIELD OR WILDCAT	NAME
3. ADDRESS OF OPERATOR P.O. Box 1206, Jal, NM 88252-1206	Jalmat Gas 11. SEC., T., R., M., OR BLK. AND SURVEY OR	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	
below.) 660 FWL & 1650 FNL, Sec. 33, T-25-S,	Sec. 33, T-25-S, R-37-E	
AT SURFACE: R-37-E AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH	13. STATE
AT TOTAL DEPTH:	Lea	New Mexico
	14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)	
DECUIECT FOR APPROVAL TO	3000.0 GL	120 000
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	7	11. 12.14.
FRACTURE TREAT		
SHOOT OR ACIDIZE	- 182 WIN	
REPAIR WELL	(NOTE: Report results of m	nultiple completion of zone
PULL OR ALTER CASING [change on Form \$	-33 0.)
MULTIPLE COMPLETE	\$1.20 kg & 6.	,
ABANDON*		$r = \frac{f}{f}$
(other) Casing & Cementing	DIST	. 6 4 N /
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is different measured and true vertical depths for all markers and zones pertiner. The well was spudded 1-12-84 Drilled 12-1/4" hole & set 382.40 of 8-5/8", casing, and cemented with 250 sx Class C, 2%	irectionally drilled, give set to this work.)* , 23#, J-55, Grade	B surface
Drilled 7-7/8" hole & set 3198.61' of 5-1/2", casing as follows:	, 15.50#, J-55, Pr	oduction
Float shoe		
Cemented with 850 sx Halliburton Lite and 250 (work accomplished 1-20-84)) sx 50/50 Poz C,	circulated 300 sx
Subsurface Safety Valve: Manu. and Type	Set	t @ Ft.
18. I hereby certify that the foregoing is true and correct		
SIGNED R.W. Lansford TITLE VP/Energy Resc		6, 1984
ACCEPTED FOR RECORPHIS space for Federal or State off APPROVED BY		
MAY 15 1984		

toff med to the second

MAY 18 1984 HOBBS OFFICE

...

;