

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name LMWU
3. Address of Operator P.O. Box 840, Seminole, Tx 79360	9. Well No. #114
4. Location of Well UNIT LETTER <u>G</u> <u>1539</u> FEET FROM THE <u>North</u> LINE AND <u>2407</u> FEET FROM THE <u>East</u> LINE, SECTION <u>33</u> TOWNSHIP <u>24S</u> RANGE <u>37E</u> N.M.P.M.	10. Field and Pool, or Wildcat Langlie Mattix Field Langlie Mattix Pool
15. Elevation (Show whether DF, RT, GR, etc.) GR 3247	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

PRODUCTION CASING (3-21-84)

5 1/2" 14# K-55 csg in 8 3/4" hole set @ 3818'. Cement with 450sx 65:35 Lite Poz + 6% gel and 300sx Class "C" + 10#/sx salt + 1/4#/sx cellophane flakes circ. 40sx cement to surface.

INTERMEDIATE CASING (3-10-84)

9 5/8" 36# K-55 Csg. in 12 1/4" hole set @ 2950'. Cement with 700sx 65:35 Lite Poz + 6% gel + 10#/sx salt and 300 sx. Class "C" + 10#/sx salt + 2% CaCl₂ circ. 180sx cement to surface.

SURFACE CASING (3-5-84)

13 3/8" 48# & 54.50# K-55 csg in 17 1/2" hole set @ 341: Cement with 500sx Class "C" + 2% CaCl₂ circ. 175sx cement to surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED S. Butler TITLE Sr. Petroleum Engineer DATE April 4, 1984

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE APR 12 1984

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
APR 11 1984
O.D.
HOBBS OFFICE