B	UN TED STATES	NT. 53240	5. LEASE DESIGNATION A NM-0766	ND BEBIAL NO	
SUNDRY (Do not use this form fo Use "A	NOTICES AND REPORTS or proposals to drill or to deepen or plug APPLICATION FOR PERMIT—" for such	ON WELLS back to a different reservoir. proposals.)	6. IF INDIAN, ALLOTTEE	OR TRIBE NAME	
			7. UNIT AGREEMENT NAME		
2. NAME OF OPERATOR		8. FARM OR LEASE NAME	8. FARM OR LEASE NAME		
Doyle Hartman 3. ADDRESS OF OPERATOR		Carlson Federal			
Post Office Box 10426 Midland, Texas 79702 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)		9. WELL NO.	9. WELL NO.		
		4 10. FIELD AND POOL, OR	WILDCAT		
990 FSL & 990 FEL (P)				Langlie Mattix	
			11. SEC., T., E., M., OR BLE. AND		
			Section 23, T-2	5-S. R-37	
4. PERMIT NO	15 ELEVATIONS (Show whether D	F, RT, GR, etc.)	12. COUNTY OF PARISH		
30-025-70400	3081.9 G.L.		Lea	13. STATE NM	
3 Cha					
	ck Appropriate Box To Indicate 1 F INTENTION TO :	1			
·	r	80	BSEQUENT REPORT OF:		
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WE	LL	
SHOOT OR ACIDIZE	MULTIPLE COMPLETE	FRACTUBE TREATMENT	ALTEBING CASI		
REPAIR WELL	CHANGE PLANS	SHOOTING OR ACIDIZING (Other) Reach TD		×	
(Other)			sults of multiple completion on completion Report and Log form.	Well	
DESCRIBE PROPOSED OR COMPLET proposed work If well is next to this work.)*	TEN OPERATIONS (Clearly state all pertiner directionally drilled, give subsurface loca	it details, and give pertipent d tions and measured and true v	lates, including estimated date of erilcal depths for all markers a) of starting any nd zones perti-	
TUTTIC, LIGO CASIN	total depth of 3800'. g and landed at 3800'.	Ran float choo and	floot		
Ran DV tool at 23 a 50-50 blend of Floseal, and 2-1/2 DV tool and circu stages. Second st burton Econolite, of a 50-50 blend of Floseal and 2-1/2 120 sx excess ceme	a total depth of 3800'. Ig and landed at 3800'. 54'. Cemented casing in API Class C cement and P 2 lb/sx Gilsonite. Plug lated 75 sx excess cemen tage consisted of 400 sx 1/4 lb/sx Floseal & 2-1 of API Class C cement and lb/sx Gilsonite. Plug ent to pit. Closed DV to y. Released pressure and	Ran float shoe and two stages. First ozmix A containing down at 7:00 p.m. t to pit. Circulat of Class C cement /2 lb/sx Gilsonite, d Pozmix A containi down at 12:45 a.m.	float collar at 37 t stage was 350 sx of 18% salt, 1/4 1b/st CDT 9-21-85. Opene ted 4 hours between containing 3% Halls followed by 200 sp ing 18% salt, 1/4 1	76'. of x ed i- k lb/sx	
Ran DV tool at 23 a 50-50 blend of Floseal, and 2-1/2 DV tool and circu stages. Second st burton Econolite, of a 50-50 blend of Floseal and 2-1/2 120 sx excess ceme	API Class C cement and P 2 lb/sx Gilsonite. Plug lated 75 sx excess cemen tage consisted of 400 sx 1/4 lb/sx Floseal & 2-1 of API Class C cement and lb/sx Gilsonite. Plug ent to pit. Closed DV to	Ran float shoe and two stages. First ozmix A containing down at 7:00 p.m. t to pit. Circulat of Class C cement /2 lb/sx Gilsonite, d Pozmix A containi down at 12:45 a.m.	float collar at 37 t stage was 350 sx of 18% salt, 1/4 1b/st CDT 9-21-85. Opene ted 4 hours between containing 3% Halls followed by 200 sp ing 18% salt, 1/4 1	76'. of x ed i- k lb/sx	
Ran DV tool at 23 a 50-50 blend of Floseal, and 2-1/2 DV tool and circu stages. Second st burton Econolite, of a 50-50 blend of Floseal and 2-1/2 120 sx excess ceme	API Class C cement and P 2 lb/sx Gilsonite. Plug lated 75 sx excess cemen tage consisted of 400 sx 1/4 lb/sx Floseal & 2-1 of API Class C cement and lb/sx Gilsonite. Plug ent to pit. Closed DV to	Ran float shoe and two stages. First ozmix A containing down at 7:00 p.m. t to pit. Circulat of Class C cement /2 lb/sx Gilsonite, d Pozmix A containi down at 12:45 a.m.	float collar at 37 t stage was 350 sx of 18% salt, 1/4 1b/st CDT 9-21-85. Opene ted 4 hours between containing 3% Halls followed by 200 sp ing 18% salt, 1/4 1	76'. of x ed i- k lb/sx	
Ran DV tool at 23 a 50-50 blend of Floseal, and 2-1/2 DV tool and circu stages. Second st burton Econolite, of a 50-50 blend of Floseal and 2-1/2 120 sx excess ceme	API Class C cement and P 2 lb/sx Gilsonite. Plug lated 75 sx excess cemen tage consisted of 400 sx 1/4 lb/sx Floseal & 2-1 of API Class C cement and lb/sx Gilsonite. Plug ent to pit. Closed DV to	Ran float shoe and two stages. First ozmix A containing down at 7:00 p.m. t to pit. Circulat of Class C cement /2 lb/sx Gilsonite, d Pozmix A containi down at 12:45 a.m.	float collar at 37 t stage was 350 sx of 18% salt, 1/4 1b/st CDT 9-21-85. Opene ted 4 hours between containing 3% Halls followed by 200 sp ing 18% salt, 1/4 1	76'. of x ed i- k lb/sx	
Ran DV tool at 23 a 50-50 blend of Floseal, and 2-1/2 DV tool and circu stages. Second st burton Econolite, of a 50-50 blend of Floseal and 2-1/2 120 sx excess ceme	API Class C cement and P 2 lb/sx Gilsonite. Plug lated 75 sx excess cemen tage consisted of 400 sx 1/4 lb/sx Floseal & 2-1 of API Class C cement and lb/sx Gilsonite. Plug ent to pit. Closed DV to	Ran float shoe and two stages. First ozmix A containing down at 7:00 p.m. t to pit. Circulat of Class C cement /2 lb/sx Gilsonite, d Pozmix A containi down at 12:45 a.m.	float collar at 37 t stage was 350 sx of 18% salt, 1/4 1b/st CDT 9-21-85. Opene ted 4 hours between containing 3% Halls followed by 200 sp ing 18% salt, 1/4 1	76'. of x ed i- k lb/sx	
Ran DV tool at 23 a 50-50 blend of Floseal, and 2-1/2 DV tool and circu stages. Second st burton Econolite, of a 50-50 blend of Floseal and 2-1/2 120 sx excess ceme	API Class C cement and P 2 lb/sx Gilsonite. Plug lated 75 sx excess cemen tage consisted of 400 sx 1/4 lb/sx Floseal & 2-1 of API Class C cement and lb/sx Gilsonite. Plug ent to pit. Closed DV to	Ran float shoe and two stages. First ozmix A containing down at 7:00 p.m. t to pit. Circulat of Class C cement /2 lb/sx Gilsonite, d Pozmix A containi down at 12:45 a.m.	float collar at 37 t stage was 350 sx of 18% salt, 1/4 1b/st CDT 9-21-85. Opene ted 4 hours between containing 3% Halls followed by 200 sp ing 18% salt, 1/4 1	76'. of x ed i- k lb/sx	
Ran DV tool at 23 a 50-50 blend of Floseal, and 2-1/2 DV tool and circul stages. Second st burton Econolite, of a 50-50 blend of Floseal and 2-1/2 120 sx excess ceme Pressure held okay	API Class C cement and P API Class C cement and P 2 lb/sx Gilsonite. Plug lated 75 sx excess cemen tage consisted of 400 sx 1/4 lb/sx Floseal & 2-1 of API Class C cement and lb/sx Gilsonite. Plug ent to pit. Closed DV to y. Released pressure and	Ran float shoe and two stages. First ozmix A containing down at 7:00 p.m. t to pit. Circulat of Class C cement /2 lb/sx Gilsonite, d Pozmix A containi down at 12:45 a.m.	float collar at 37 t stage was 350 sx of 18% salt, 1/4 1b/st CDT 9-21-85. Opene ted 4 hours between containing 3% Halls followed by 200 sp ing 18% salt, 1/4 1	76'. of x ed i- k lb/sx	
Ran DV tool at 23 a 50-50 blend of Floseal, and 2-1/2 DV tool and circul stages. Second st burton Econolite, of a 50-50 blend of Floseal and 2-1/2 120 sx excess ceme Pressure held okay	API Class C cement and P API Class C cement and P 2 lb/sx Gilsonite. Plug lated 75 sx excess cemen tage consisted of 400 sx 1/4 lb/sx Floseal & 2-1 of API Class C cement and lb/sx Gilsonite. Plug ent to pit. Closed DV to y. Released pressure and	Ran float shoe and two stages. First ozmix A containing down at 7:00 p.m. t to pit. Circulat of Class C cement /2 lb/sx Gilsonite, d Pozmix A containi down at 12:45 a.m. bol and pressure te d float held okay.	float collar at 37 t stage was 350 sx of 18% salt, 1/4 1b/ss CDT 9-21-85. Opene ted 4 hours between containing 3% Halls followed by 200 sp ing 18% salt, 1/4 1 CDT 9-22-85. Circu ested casing to 1500 SEP25 1985	76'. of x ed i- k lb/sx	
Ran DV tool at 23 a 50-50 blend of Floseal, and 2-1/2 DV tool and circul stages. Second st burton Econolite, of a 50-50 blend of Floseal and 2-1/2 120 sx excess ceme Pressure held okay	API Class C cement and P API Class C cement and P 2 lb/sx Gilsonite. Plug lated 75 sx excess cemen tage consisted of 400 sx 1/4 lb/sx Floseal & 2-1 of API Class C cement and lb/sx Gilsonite. Plug ent to pit. Closed DV to y. Released pressure and	Ran float shoe and two stages. First ozmix A containing down at 7:00 p.m. t to pit. Circulat of Class C cement /2 lb/sx Gilsonite, d Pozmix A containi down at 12:45 a.m.	float collar at 37 t stage was 350 sx of 18% salt, 1/4 1b/ss CDT 9-21-85. Opene ted 4 hours between containing 3% Halls followed by 200 sp ing 18% salt, 1/4 1 CDT 9-22-85. Circu ested casing to 1500 SEP25 1985	76'. of x ed i- x lb/sx ulated) psi.	
Ran DV tool at 23 a 50-50 blend of Floseal, and 2-1/2 DV tool and circul stages. Second st burton Econolite, of a 50-50 blend of Floseal and 2-1/2 120 sx excess ceme Pressure held okay	API Class C cement and P 2 lb/sx Gilsonite. Plug lated 75 sx excess cemen tage consisted of 400 sx 1/4 lb/sx Floseal & 2-1 of API Class C cement and lb/sx Gilsonite. Plug ent to pit. Closed DV to y. Released pressure and Manual Manual Man	Ran float shoe and two stages. First ozmix A containing down at 7:00 p.m. t to pit. Circulat of Class C cement /2 lb/sx Gilsonite, d Pozmix A containi down at 12:45 a.m. bol and pressure te d float held okay.	float collar at 37 t stage was 350 sx of 18% salt, 1/4 1b/ss CDT 9-21-85. Opene ted 4 hours between containing 3% Halls followed by 200 sp ing 18% salt, 1/4 J CDT 9-22-85. Circu ested casing to 1500 SEP25 1985	76'. of x ed i- x lb/sx ulated) psi.	
Ran DV tool at 23 a 50-50 blend of Floseal, and 2-1/2 DV tool and circu stages. Second st burton Econolite, of a 50-50 blend of Floseal and 2-1/2 120 sx excess ceme Pressure held okay	API Class C cement and P 2 lb/sx Gilsonite. Plug lated 75 sx excess cemen tage consisted of 400 sx 1/4 lb/sx Floseal & 2-1 of API Class C cement and lb/sx Gilsonite. Plug of ent to pit. Closed DV to y. Released pressure and API Class C cement and to pit. Closed DV to pressure and data description of the top the top of the top of to	Ran float shoe and two stages. First ozmix A containing down at 7:00 p.m. t to pit. Circulat of Class C cement /2 lb/sx Gilsonite, d Pozmix A containi down at 12:45 a.m. bol and pressure te d float held okay.	float collar at 37 t stage was 350 sx of 18% salt, 1/4 1b/ss CDT 9-21-85. Opene ted 4 hours between containing 3% Halls followed by 200 sp ing 18% salt, 1/4 J CDT 9-22-85. Circu ested casing to 1500 SEP25 1985	76'. of x ed i- x lb/sx ulated) psi.	
Ran DV tool at 23 a 50-50 blend of Floseal, and 2-1/2 DV tool and circul stages. Second st burton Econolite, of a 50-50 blend of Floseal and 2-1/2 120 sx excess ceme Pressure held okay	API Class C cement and P 2 lb/sx Gilsonite. Plug lated 75 sx excess cemen tage consisted of 400 sx 1/4 lb/sx Floseal & 2-1 of API Class C cement and lb/sx Gilsonite. Plug of ent to pit. Closed DV to y. Released pressure and Nemere TITLE Adm e office use) Trine RECORD TITLE MWR	Ran float shoe and two stages. First ozmix A containing down at 7:00 p.m. t to pit. Circulat of Class C cement /2 lb/sx Gilsonite, d Pozmix A containi down at 12:45 a.m. bol and pressure te d float held okay.	float collar at 37 t stage was 350 sx of 18% salt, 1/4 lb/sz CDT 9-21-85. Openent ted 4 hours between containing 3% Hall: followed by 200 sz ing 18% salt , 1/4 J CDT 9-22-85. Circu ested casing to 1500 SEP.25 198 407 9-24-85 DATE 9-24-85	76'. of x ed i- x lb/sx ulated) psi.	

Title 18 U.S.C. Sex on 1001, makes it a crime ter any person knowingly and willfully to make to any department or agency of the United States any failed, fictitious of fraudulent statements or representations as to any matter within its jurisdiction.

••



(