

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Sun Exploration & Production Co.
3. ADDRESS OF OPERATOR
P. O. Box 1861, Midland, Texas 79702
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) Unit Letter c, 660' FNL & 1980 FWL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>

(other) Set 9-5/8" csg at 5240' - New Well

5. LEASE
NM28315
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Pitchfork Federal
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Pitchfork Ranch (Morrow)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 11, T-25-S, R-34-E
12. COUNTY OR PARISH
Lea
13. STATE
New Mexico
14. API NO.
30-025-29665
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3361.0' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-21-86 R & C 119 jts 9-5/8" csg, CS 5240', FC 5198'. Howco cmt'd w/1500 sxs Howco Lite w/10% salt + 1/4# flocele, followed by 400 sxs "C" w/10% salt, PD at 10 AM, FP 1800-2500, float held, circ 296 sxs, J.C. @ 10AM. ND BOP, set slips, cut off 9-5/8" csg, tst csg, blind rams and manifold to 2500# for 1/2 hr, O. K. TIH w/BHA and DP, test rams to 2500# for 1/2 hr O. K. Now drilling ahead.

5-26-86 Now drilling in lime at 8707'.

ACCEPTED FOR RECORD

MAY 29 1986

CARLSBAD, NEW MEXICO

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Maria L. Perez TITLE Sr. Acctng. Asst DATE 5-27-86
915-688-0375

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: