

Supplemental Drilling Data
Sirgo-Collier, Inc.
WDQSU 30 #8
2350' FSL, 150' FEL, Section 30, T-24-S, R-38-E
Unit I, Lea County, New Mexico

1. Surface Formation: Tertiary Pliocene, GL 3161⁷²
2. Estimated Tops of Geologic Markers:

Rustler	1140'	T/Yates	2765'
Top/Salt	1300'	T/Queen	3677'
Base/Salt	2580'	Grayburg	3875'
3. Anticipated Porosity Zones: Queen 3677' Oil
4. Casing Design:

<u>Size</u>	<u>Interval</u>	<u>Weight</u>	<u>Grade</u>	<u>Joint</u>
8-5/8"	0 - 400'	24.0#	J-55	STC
5-1/2"	0 - 2100' 3350'	15.50#	J-55	STC
5. Surface Control Equipment: Double RAM-type, Series 900 + BOP with annular (See Exhibit).
6. Circulating Medium: Native, cut brine conditioned as necessary for control of viscosity and water loss.
7. Auxiliary Equipment: None
8. Testing, Logging and Coring Programs: Electric Logs - Dual Laterlog/MICRO Laterlog/Gamma Ray/Caliper Compensated Density Log. Possible core from 3750' - 3850'.
9. Abnormal Pressure, Temperature or Gases: None anticipated.
10. Anticipated Starting Date: Operations will commence upon approval approximately May 5, 1987. Duration of drilling, completion and testing, about 5 weeks.