

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

U.S. OIL CONS. COMMISSION
P.O. BOX 1980
HOBBS, NEW MEXICO 88240

LEASE DESIGNATION AND SERIAL
LC-067968

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME WDSU West Dollarhide
2. NAME OF OPERATOR Sirgo-Collier, Inc.	8. FARM OR LEASE NAME Queen Land Unit
3. ADDRESS OF OPERATOR P. O. Box 3531, Midland, Texas 79702	9. WELL NO. 30-77
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below) At surface 1100' FSL 2450' FEL, Sec 30, T-24-S, R-38-E	10. FIELD AND POOL OR WILDCAT Dollarhide Queen
14. PERMIT NO.	11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA Sec 30, T-24-S, R-38-E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) GL 3120' KB 3131.5'	12. COUNTY OR PARISH Lea
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO		SUBSEQUENT REPORT OF	
TEST WATER SHUT OFF	PULL OR ALTER CASING	WATER SHUT OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL	CHANGE PLANT	(Other) Spud, cement surface & prod. string	
(Other)		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. (If work proposed or completed, operations other than drilling, state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-31-87 Spudded with 12-1/4" bit to TD of 425' KB.

8-1-87 Ran 425' (14 joints) of 8-5/8" 24# J grade casing, type M slotted shoe and 3 centralizers. Cemented 250 sx of Class C cement with 2% CaCl2. Circulated 60 sx to pit.

8-1-87 Tested 8-5/8" 800#, 30 minutes. Test okay.

8-7-87 TD 3873' KB.

8-8-87 Ran 3869' (108 joints) 5-1/2" 15.50# J grade casing. Cemented with 800 sx Halliburton Light + 200 sx Class C cement, 15# salt, 1/4# Flocele, and 2% CaCl2. Circulated 138 sx to pit

ACCEPTED FOR RECORD

SJS

AUG 31 1987

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Amy L. Whitley

TITLE Agent

DATE 8-19-87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED

SEP 8 1987

**OCD
HOBBS OFFICE**