

LC-069052

6 IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME WDQSU
2. NAME OF OPERATOR Sirgo-Collier, Inc.	8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR P. O. Box 3531, Midland, Texas 79702	9. WELL NO. 31-78
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below) At surface Unit A, 100' FNL 1180' FEL, Sec 31, T-24-S, R-38-E	10. FIELD AND POOL OR WILDCAT Dollarhide Queen
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 31, T-24-S, R-38-E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) GL 3138' KB 3149.5'	12. COUNTY OR PARISH Lea
	13. STATE NM

16 Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT OFF	PULL OR ALTER CASING
FRACTURE TREAT	MULTIPLE COMPLETE
SHOOT OR ACIDIZE	ABANDON*
REPAIR WELL	CHANGE PLANT
(Other)	

SUBSEQUENT REPORT OF:

WATER SHUT OFF	REPAIRING WELL
FRACTURE TREATMENT	ALTERING CASING
SHOOTING OR ACIDIZING	ABANDONMENT*
(Other) Spud, cement surface & prod. string	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17 DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

- 8-8-87 Spudded with 12-1/4" bit to TD of 425' KB. Ran 422' of 8-5/8" 24# J grade casing, type M slotted shoe and 3 centralizers. Cemented 250 sx Class C cement + 2% CaCl2 and circulated 68 sx to pit.
- 8-9-87 Tested 8-5/8" 600#. Test okay
- 8-14-87 TD 3852' KB
- 8-15-87 Ran 3852' of 5-1/2" 15.50# J grade casing. Cemented with 800 sx Halliburton Light + 200 sx Class C cement + 15# salt, 1/4# Flocele + 2% CaCl2. Circulated 120 sx to pit.

ACCEPTED FOR RECORD

AUG 31 1987

SJS

CARLSBAD, NEW MEXICO

AUG 25 10 50 AM '87

RECEIVED

18 I hereby certify that the foregoing is true and correct

SIGNED

Amy L. Whitley

TITLE Agent

DATE 8-24-87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED

SEP 8 1987

OCB
HOBBS OFFICE