

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
Sirgo-Collier, Inc.

3. ADDRESS OF OPERATOR
P. O. Box 3531, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface
Unit J, 2310' FSL 2600' FEL, Sec 30, T-24-S, R-38-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
GL 3123' KB 3134.5'

5. LEASE DESIGNATION AND SERIAL NO.
LC-067968

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
West Dollarhide Queen
WDSU - Hand unit

8. FARM OR LEASE NAME

9. WELL NO.
30-79

10. FIELD AND POOL, OR WILDCAT
Dollarhide Queen

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 30, T-24-S, R-38-E

12. COUNTY OR PARISH
Lea

13. STATE
NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO		SUBSEQUENT REPORT OF	
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ABANDON	ABANDON*	SHOOTING OR ABANDONING	ABANDONMENT*
DEEPEN WELL	CHANGE PLANS	OTHER	Spud, cement surface & prod. string.

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.*
- 8-15-87 Spudded with 12-1/4" bit to TD of 429' KB. Ran 425' of 8-5/8" 24# J grade casing, type M slotted shoe and 3 centralizers. Cemented 250 sx Class C cement + 5 sx CaCl2 and circulated 50 sx to pit.
 - 8-16-87 Tested 8-5/8" 600#. Test okay.
 - 8-21-87 TD 3910' KB
 - 8-22-87 Ran 3910' of 5-1/2" 15.50# J grade casing. Cemented with 900 sx Halliburton Light cement + 200 sx Class C + 15# salt + 1/4# Flocele + 2% CaCl2. Circulated 165 sx to pit.

ACCEPTED FOR RECORD

SEP 10 1987

SJS

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNATURE Amy L. Whitley TITLE Agent

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE 8-31-87

CONDITIONS OF APPROVAL, IF ANY: _____

*See Instructions on Reverse Side

RECEIVED
SEP 1 10 56 AM '87
CARLSBAD, NEW MEXICO

RECEIVED

SEP 14 1961

CCD
HOBBS OFFICE