

(November 1985)
(Formerly 9--331)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instruction
reverse side)

Expires August 31, 1985
5. LEASE DESIGNATION AND SERIAL NO.
LC-067968
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. NAME OF OPERATOR
Sirgo-Collier, Inc.
3. ADDRESS OF OPERATOR
P. O. Box 3531, Midland, Texas 79702
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
Unit H, 1700' FNL 330' FEL, Sec. 30, T-24-S, R-38-E

7. UNIT AGREEMENT NAME
WDQSU
8. FARM OR LEASE NAME

9. WELL NO.
30-81
10. FIELD AND POOL, OR WILDCAT
Dollarhide Queen
11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)
GL 3182' KB 3193.5'
12. COUNTY OR PARISH 13. STATE
Lea NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANE ☐
(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☐
(Other) Spud, cement surface and prod. string
(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-30-87 Spudded with 12½" bit to TD of 437' KB
Ran 431' of 8-5/8" 24# J grade casing, type M slotted shoe and
3 centralizers. Cemented 250 sx Class C cement with 2% CaCl2.
Circulated 25 sx to pit.
8-31-87 Tested 8-5/8" casing to 600#. Tested okay.
9-4-87 TD 4030' KB
9-5-87 Ran 4030' of 5½" 17# J grade casing. Cemented with 800 sx
Halliburton Light + 200 sx Class C cement, 15# salt, 1/4# Flocele
and 2% CaCl2. Circulated 112 sx to pit.

ACCEPTED FOR FILE

SEP 28 1987

SJS

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED Amy L. Whitley TITLE Agent DATE 9-22-87
(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side