

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-9519	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name West Dollarhide Queen Sand Unit
2. Name of Operator Sirgo-Collier, Inc.		8. Farm or Lease Name
3. Address of Operator P. O. Box 3531, Midland, Texas 79702		9. Well No. 83
4. Location of Well UNIT LETTER <u>E</u> <u>1700</u> FEET FROM THE <u>North</u> LINE AND <u>1000</u> FEET FROM THE <u>West</u> LINE, SECTION <u>29</u> TOWNSHIP <u>24-S</u> RANGE <u>38-E</u> NMPM.		10. Field and Pool, or Wildcat Dollarhide Queen
15. Elevation (Show whether DF, RT, GR, etc.) GL 3213' KB 3224.5'		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER Spud, cement surface & production string ☒

17822396

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-12-87 Spudded with 12 $\frac{1}{4}$ " bit to TD of 450'
9-13-87 Ran 450' of 8-5/8" 24# J grade casing, type M slotted shoe and 3 centralizers. Cemented 250 sx Class C cement with 2% CaCl₂. Circulated 22 sx to pit. Tested 8-5/8" casing to 600#. Tested okay.
9-19-87 TD 4076'
9-20-87 Ran 4076' of 5 $\frac{1}{2}$ " 15.50 & 17# J grade casing. Cemented with 800 sx Halliburton Light + 200 sx Class C cement, 15# salt, 1/4# Flocele and 2% CaCl₂. Circulated 230 sx to pit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Amy L. Whitley TITLE Agent DATE 10-06-87

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE OCT 9 1987

CONDITIONS OF APPROVAL, IF ANY: