

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-77

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.

B-9613

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER	7. Unit Agreement Name
2. Name of Operator TEXACO PRODUCING INC	8. Farm or Lease Name WEST DOLLARHIDE DRINKARD UNIT
3. Address of Operator P.O. BOX 728, HOBBS, NEW MEXICO 88240	9. Well No. 95
4. Location of Well UNIT LETTER C 75 FEET FROM THE NORTH LINE AND 1410 FEET FROM THE WEST LINE, SECTION 32 TOWNSHIP 24S RANGE 38E NMPM.	10. Field and Pool, or Wildcat DOLLARHIDE TUBB DRINKARD
15. Elevation (Show whether DF, RT, GR, etc.)	12. County LEA

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER OPENHOLE LOGGING FROM PRODUCTION CSG ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

ON DECEMBER 18, 1987 T.O.D. 778" HOLE @ 6:15 P.M. 6950' BOTTOM TO 4" RAN OPEN HOLE LOGS 1. GR-CAL DLL-MICROGUARD (GR 6947' TO SURFACE; CAL 6947' TO 3050'; DLL-MICROGUARD 6947' TO 4947') 2. SPECTRAL DENSITY DUAL SPACED NEUTRON LOG 6947' TO 4900'. 3. MULTISSET TESTER LOG 6901'-6330'. RIG DOWN LOGGERS. RAN 170 JTS 5 1/2", 15.5" & 17" J-55 LT & C CASING. FC @ 6867. FS @ 6950' DV TOOL @ 4021. CEMENT 1ST STAGE 400SX LITE WEIGHT (12.4") CLASS H & 1/4" FLOCELE TAILED w/200SX CLASS H & 1/4" FLOCELE (15.6") CIRC 43SX TO PIT 2ND STAGE 400SX LITE WEIGHT (12.4") CLASS H & 1/4" FLOCELE TAILED w/200SX CLASS H & 1/4" FLOCELE (15.6") CIRC 70SX TO PIT. MOVE RIG OFF (WOC 18 HRS) MIRU. DRILL OUT CEMENT AND FC (6375' TO 6930') TEST CSG TO 1500PSI. HELD OKAY 30 MINUTES. RIG UP LOGGERS. RUN GR-CBL-CCL (6930' PBID TO 4900') GOOD BOND.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED K. Johnson TITLE AREA SUPERINTENDENT DATE JAN 7 1988

APPROVED BY Orig. Signed by Paul Kautz Geologist TITLE DATE JAN 17 1988

CONDITIONS OF APPROVAL, IF ANY: