

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPL
(Other instructions
verse side)

"E"
re-

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO
LC-069052

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Sirgo-Collier, Inc.

3. ADDRESS OF OPERATOR

P. O. Box 3531, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

Unit G, 2450' FNL 1350' FEL, Sec. 31, T-24-S, R-38-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GL 3127' KB 3138.5'

7. UNIT AGREEMENT NAME

West Dollarhide Queen
WDQSU Sand Unit

8. FARM OR LEASE NAME

9. WELL NO.

31-87

10. FIELD AND POOL, OR WILDCAT

Dollarhide Queen

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 31, T24S, R38E

12. COUNTY OR PARISH

Lea

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Spud, cement surface & prod. strings.

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.) *

10-12-87 Spudded with 12 $\frac{1}{4}$ " bit to TD of 430'. Ran 430' of 8-5/8" 24# J grade casing, type M slotted shoe, and 3 centralizers. Cemented with 250 sx Class "C" cement and circulated 75 sx to pit.

10-13-87 Tested 8-5/8" casing to 800#. Tested okay.

10-17-87 TD 3850'

10-19-87 Ran 3850' of 5 $\frac{1}{2}$ " 15.50 & 17# J grade casing. Cemented with 800 sx Halliburton Light + 200 sx Class "C" cement. Circulated 260 sx to pit.

ACCOMPLISHED

SJS

NOV 2 1987

RECEIVED
OCT 20 1 31 PM '87
CARRIZO
AREA HEADQUARTERS

18. I hereby certify that the foregoing is true and correct

SIGNED Amey L. Whitley

TITLE Agent

DATE 10-19-87

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED

OCT 30 1987

OCD

HOBBS OFFICE