

(November 1983)
(Formerly 9-331)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPL
(Other Instructions
verse side)

FE
10

Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-069052

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
Sirgo-Collier, Inc.

3. ADDRESS OF OPERATOR
P. O. Box 3531, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
Unit H, 1450' FNL 250' FEL, Section 31, T24S, R38E

7. UNIT AGREEMENT NAME
WDQSH *West Dollarhide*

8. FARM OR LEASE NAME
Queen Sand Unit

9. WELL NO.
H-88

10. FIELD AND POOL, OR WILDCAT

Dollarhide Queen
11. SEC., T., S., M., OR BLK. AND SURVEY OR AREA

Sec. 31, T24S, R38E

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)
GL 3147' KB 3158.5'

12. COUNTY OR PARISH 13. STATE
Lea NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) *Spud, cement surface & prod. casing.*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-19-87 Spudded with 12-1/4" bit to TD of 420'. Ran 9 joints 8-5/8" 24# casing to 416'. Cemented with 250 sx Class C, circ. 45 sx to pit.

10-20-87 Tested BOP and casing to 600# for 30 min. Tested okay.

10-24-87 TD 3880'

10-25-87 Ran 93 joints 5-1/2" 15.5 & 17# casing to 3880'. Cemented with 800 sx Halliburton Lite, tailed with 200 sx Class C. PD at 9:30 am. Circ. 104 sx to pit.

RECEIVED
NOV 17 10 40 AM '87
BUREAU OF LAND MANAGEMENT
WASHINGTON, D.C.

18. I hereby certify that the foregoing is true and correct

SIGNED *Amy L. Whitley* TITLE Agent

DATE 11-13-87

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side