

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name West Dollarhide Queen Sand Unit
Name of Operator Sirgo-Collier, Inc.	8. Farm or Lease Name
Address of Operator P. O. Box 3531, Midland, Texas 79702	9. Well No. 103
Location of Well UNIT LETTER <u>F</u> , <u>1560</u> FEET FROM THE <u>North</u> LINE AND <u>1610</u> FEET FROM THE <u>West</u> LINE, SECTION <u>30</u> TOWNSHIP <u>24S</u> RANGE <u>38E</u> N.M.P.M.	10. Field and Pool, or Wildcat Dollarhide Queen
15. Elevation (Show whether DF, RT, GR, etc.) 3119' GR 3130.5' KB	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
DRILL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER Spud, cement surface & prod. strings <input checked="" type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 12-25-87 Spudded with 12-1/4" bit to TD of 422'. Ran 12 joints of 8-5/8" casing to 418'. Cemented with 250 sx Class "C" + 2% KCl. PD @ 12:45 am 12-26-87. Circulated 65 sx.
- 12-27-87 Tested BOP & casing to 800#. Tested okay.
- 12-30-87 TD 4035'
- 12-31-87 Ran 120 joints 5-1/2" 17# casing to 4035'. Cemented with 800 sx Halliburton Lite + 200 sx Class "C". PD @ 12:30 am 1-1-88. Circulated 150 sx.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Amy L. Whitley TITLE Agent DATE January 5, 1988

Orig. Signed by  
Paul Kautz  
Geologist

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: