

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
P. O. BOX 100
HOBBS, NEW MEXICO 88240

Form approved.
Budget Bureau No. 1004-01-3
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-069052

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER Water injection well
2. NAME OF OPERATOR
Sirgo-Collier, Inc.
3. ADDRESS OF OPERATOR
P. O. Box 3531, Midland, Texas 79702
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
Unit C, 330' FNL 2360' FWL, Sec. 31, T24S, R38E

7. UNIT AGREEMENT NAME

WDQSU

8. FARM OR LEASE NAME

9. WELL NO.

113

10. FIELD AND POOL, OR WILDCAT

Dollarhide Queen

11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA

Sec. 31, T24S, R38E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3108' GR

12. COUNTY OR PARISH

Lea

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Spud, cmt surf. & injec. csg. XX

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-13-88 Spudded with 12-1/4" bit to TD of 398'. Ran 10 joints 8-5/8" 24# casing to 398'. Cemented with 250 sx Class "C" with 2% CaCl2. Circulated 53 sx.

2-19-88 TD 3910'.

2-20-88 Ran 127 joints of 5-1/2" 17# casing to 3910'. Cemented with 900 sx Halliburton Light with 15# salt and 1/4# flocele, tailed with 200 sx Class "C" with 2% CaCl2. Circulated 106 sx.

18. I hereby certify that the foregoing is true and correct

SIGNED Amey L. Whitley

TITLE Agent

DATE March 3, 1988

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

*See Instructions on Reverse Side

SJS