

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State ☒ Fee ☐

5. State Oil & Gas Lease No.  
B-9311

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name West Dollarhide Queen Sand Unit
2. Name of Operator Sirgo-Collier, Inc.	8. Farm or Lease Name
3. Address of Operator P. O. Box 3531, Midland, Texas 79702	9. Well No. 114
4. Location of well UNIT LETTER N 115 FEET FROM THE South LINE AND 2338 FEET FROM TWP West LINE, SECTION 32 TOWNSHIP 24S RANGE 38E NMPM.	10. Field and Pool, or Whicat Dollarhide Queen
15. Elevation (Show whether DF, RT, GR, etc.) 3143' GR 3154.5' KB	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER Spud, cement surface & prod. casing <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-13-88 Spudded with 12-1/4" bit to TD of 422'. Ran 14 joints 8-5/8" 24# casing to 416'. Cemented with 250 sx Class "C" + 2% CaCl2. PD 2:15 pm. Circulated 60 sx. WOC 18 hours.

3-14-88 Test BOP and casing to 800# for 30 minutes. Tested okay.

3-21-88 TD 3913'. Ran 102 joints 5-1/2" 17# casing to 3913'. Cemented with 650 sx Halliburton Light + 1/4# flocele + 15# salt, tailed with 200 sx Class "C" + 2% CaCl2. PD 10:00 pm. Circulated 80 sx.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Amy L. Whitley TITLE Agent DATE March 23, 1988

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT 1 SUPERVISOR TITLE  DATE

CONDITIONS OF APPROVAL, IF ANY:

HOBBY OFFICE  
OCD  
MAR 24 1988