

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPL
(Other instructions
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	5. LEASE DESIGNATION AND SERIAL NO. NM-10189
2. NAME OF OPERATOR Hondo Oil & Gas Company	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 2208, Roswell, NM 88202	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FNL & 660' FEL	8. FARM OR LEASE NAME McClure "B"
14. PERMIT NO.	9. WELL NO. 24
15. ELEVATIONS (Show whether DF, RT, OR, etc.) 3175' GL	10. FIELD AND POOL, OR WILDCAT Dollarhide Queen
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 30-T24S-R38E
	12. COUNTY OR PARISH Lea
	13. STATE NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	FULL OR ALTER CASING
FRACTURE TREAT	MULTIPLE COMPLETE
SHOOT OR ACIDIZE	ABANDON*
REPAIR WELL	CHANGE PLANS
(Other)	

WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREATMENT	ALTERING CASING
SHOOTING OR ACIDIZING	ABANDONMENT*
(Other)	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spudded well @ 12:45 p.m. 7/11/88. Drilled 12 1/4" hole to 425'. Ran 10 jts. 8 5/8" 23# X-42 Newport csg. and set @ 425'. Cemented w/250 sx. Class "C" w/2% CaCl. Circulated 59 sx. Plug down @ 11:45 p.m. 7/11/88. WOC 18 1/4 hrs. Drilled out shoe. Tested BOP to 600 psi - held okay. Drilled out w/7 7/8" bit 7/13/88.

RECEIVED
JUL 22 11 20 AM '88
CARTER
AREA

xc: B. Stubbs, J. Handley, File

18. I hereby certify that the foregoing is true and correct

SIGNED E. L. Butts Jr.

TITLE Engineer

DATE 7/21/88

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE 7/21/88
fe. ter. W. Chester
JUL 27 1988

*See Instructions on Reverse Side