

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	912'	T. Canyon	
T. Salt	1050'	T. Strawn	
B. Salt	2260'	T. Atoka	
T. Yates	2392'	T. Miss	
T. 7 Rivers	2668'	T. Devonian	
T. Queen	3132'	T. Silurian	
T. Grayburg	3395'	T. Montoya	
T. San Andres		T. Simpson	
T. Glorieta		T. McKee	
T. Paddock		T. Ellenburger	
T. Blinberry		T. Gr. Wash	
T. Tubb		T. Delaware Sand	
T. Drinkard		T. Bone Springs	
T. Abo		T.	
T. Wolfcamp		T.	
T. Penn		T.	
T. Cisco (Bough C)		T.	

Northwestern New Mexico

T. Ojo Alamo		T. Penn. "B"	
T. Kirtland-Fruitland		T. Penn. "C"	
T. Pictured Cliffs		T. Penn. "D"	
T. Cliff House		T. Leadville	
T. Menefee		T. Madison	
T. Point Lookout		T. Elbert	
T. Mancos		T. McCracken	
T. Gallup		T. Ignacio Otzte	
Base Greenhorn		T. Granite	
T. Dakota		T.	
T. Morrison		T.	
T. Todilto		T.	
T. Entrada		T.	
T. Wingate		T.	
T. Chinle		T.	
T. Permian		T.	
T. Penn "A"		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from.....3140'	to.....3160'	No. 3, from.....3245'	to.....3285'
No. 2, from.....3203'	to.....3224'	No. 4, from.....3310'	to.....3380'

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....NONE	to.....feet.....
No. 2, from.....	to.....feet.....
No. 3, from.....	to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0'	600'	600'	Lime, Shale, Sand				
600'	912'	312'	Red Beds				
912'	1050'	138'	Anhydrite & Red Bed				
1050'	2290'	1240'	Anhydrite, Salt & Red Bed				
2290'	2400'	110'	Dolomite & Anhydrite				
2400'	TD	1020'	Sand, Anhydrite, & Dolomite				