

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-30870
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Red Cloud
8. Well No. 2
9. Pool name or Wildcat Jalmat
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3155.2' G.L.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER
2. Name of Operator Tahoe Energy, Inc.
3. Address of Operator 3909 W. Industrial, Midland, Texas 79703
4. Well Location Unit Letter <u>M</u> : <u>660</u> Feet From The <u>South</u> Line and <u>660</u> Feet From The <u>West</u> Line Section <u>3</u> Township <u>25-S</u> Range <u>37-E</u> NMPM Lea County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	
OTHER: <u>Completion Procedure</u> <input checked="" type="checkbox"/>	

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <u>Logs & Production Casing</u> <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1.) Drilled 7-7/8" hole to a total depth of 3197'.
- 2.) Ran Schlumberger Dual Laterolog & Compensated Sonic Logs.
- 3.) Ran 76 jts. 4-1/2" 10.5# STC csg. set @ 3193'.
- 4.) Western Co. cemented w/425 sx. Premium Pacesetter Lite "C" + 6% gel + .25#/sx Cello-seal + 225 sx. 50:50 Poz Class "C" + 2% gel + 9#/sx. salt. Plug down @ 7:05 A.M. 5/01/90, Circulated 22 sx. to surface.
- 5.) Will perforate and treat Yates/Seven Rivers production intervals selected from Mud Log, and Schlumberger open hole logs.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE K. A. Freeman TITLE President DATE 5/02/90
TYPE OR PRINT NAME K. A. Freeman TELEPHONE NO.

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

MAY 4 1990