

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

AUG 15 10 40 AM '91

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry into a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit F, 2310' FNL & 1650' FWL, Sec. 14-T25S-R32E

5. Lease Designation and Serial No.

NM 15680

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Paduca AIU Federal #1

9. API Well No.

30-025-31177

10. Field and Pool, or Exploratory Area

Paduca Delaware

11. County or Parish, State

Lea, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Perforate, Treat, Plugback
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

5-25-91 - 7-8-91. Pumped well and tested.

7-9-91. RUPU. Perforated 7814-17'; 7822-32' (1 SPF) w/15 .50" holes. Acidized perfs 7814-32' w/3000g. 7½% NEFE acid. Swabbed well, no shows.

7-16-91. Set CIBP @ 7760' w/35' cement cap. Perforated 4 - .50" squeeze holes @5000'. Set cement retainer at 4950'. Test and establish pump-in circulation. Squeeze w/200 sx Class "C" w/additives.

7-19-91. Perforated 4797-4834' w/10 .50" holes as follows: 4797, 98, 4802, 03, 04, 30, 31, 32, 33, and 4834'. Acidized perfs 4797-4834' w/2500 g. 7½% NEFE acid.

7-20-91 - 8-10-91. Swabbed well. No show of oil on last 2 runs.

14. I hereby certify that the foregoing is true and correct

Signature [Signature]

Title Production Supervisor

Date 8-14-91

(This space for Federal or State office use)

Approved by _____

Title _____

Date _____

Conditions of approval, if any: