

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FNL & 1650' FWL, Sec. 14-T25S-R32E

5. Lease Designation and Serial No.

NM 15680

6. If Indian, Allottee or Tribe Name

-----

7. If Unit or CA, Agreement Designation

-----

8. Well Name and No.

Paduca AIU Federal #1

9. API Well No.

30-025-31177

10. Field and Pool, or Exploratory Area

Paduca Delaware

11. County or Parish, State

Lea, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other \_\_\_\_\_
- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☒ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 26" hole 11:00 AM 4-7-91. Set 39' of 20" conductor and cemented w/3-1/2 yds redi-mix. Notified BLM, Hobbs, NM, of spud. Resumed drilling 17 1/2" hole 9:00 PM 4-9-91. Ran 19 joints 13-3/8" 54.5# J-55 ST&C casing set 816'. Guide shoe set 816', insert float set 772'. Cemented w/600 sx Pacesetter Lite + 2% CaCl + 1/4#/sx Celloseal (yield 1.76, wt 12.8). Tailed in w/200 sx "C" Neat + 2% CaCl + 1/4#/sx Celloseal (yield 1.33, wt 14.8). PD 5:15 AM 4-11-91. Bumped plug to 550 psi, held okay. Circulated 83 sacks to surface. WOC. Notified Danny Cortez, BLM, Hobbs, NM to witness - no witness. Drilled out 12:45 AM 4-12-91. WOC 19 hours, 30 minutes. NU and tested to 500 psi for 30 mins, OK. Reduced hole to 11". Resumed drilling.

AG

14. I hereby certify that the foregoing is true and correct

Signed

(This space for Federal or State office use)

Title Production Supervisor

Date 4-12-91

Approved by

Conditions of approval, if any:

Title

Date