

Submit 3 Copies
to Appropriate
District Office

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Benas Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-103
Revised 1-1-89

WELL API NO.
30-025-31482

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
B-9613

7. Lease Name or Unit Agreement Name
WEST DOLLARHIDE DRINKARD UNIT

8. Well No.
113

9. Pool name or Wildcat
DOLLARHIDE TUBB DRINKARD

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
TEXACO EXPLORATION AND PRODUCTION INC.

3. Address of Operator
P. O. Box 3109 Midland, Texas 79702

4. Well Location
Unit Letter M : 136 Feet From The SOUTH Line and 1246 Feet From The WEST Line
Section 32 Township 24-SOUTH Range 38-EAST NMPM LEA County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
GR-3140', KB-3158'

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: PRODUCTION CASING ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. DRILLED 7 7/8 HOLE TO 7435'. TD @ 12:15pm 10-02-92.
2. HALLIBURTON LOGGED: RAN GR-DDL-MSFL-SONIC-CAL, GR-CNL-LDT-CAL FROM 7435' TO 4200'. RAN GR-CAST FROM 7424' TO 4800'. PULLED GR TO SURFACE.
3. RAN 5 1/2, LTC CASING (90 JTS OF 15.5 J-55, 26 JTS OF 17# J-55, 46 JTS OF 17# L-80, 6 JTS OF 17# SS-95) SET @ 7435'. RAN 20 CENTRALIZERS.
4. DOWELL CEMENTED WITH 650 SACKS 35/65 POZ CLASS H w/ 6% GEL, 5% SALT & 1/4# FLOCELE (12.8ppg, 1.87cf/s). F/B 520 SACKS CLASS H (15.6ppg, 1.18cf/s). PLUG DOWN @ 11:15am 10-04-92. DID NOT CIRCULATE.
5. RAN TEMPERATURE SURVEY. TOP OF CEMENT @ 200'.
6. ND. RELEASE RIG @ 3:30pm 10-04-92.
7. PREP TO COMPLETE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE C. P. Basham / cwt TITLE DRILLING OPERATIONS MANAGER DATE 10-05-92

TYPE OR PRINT NAME C. P. BASHAM

TELEPHONE NO. 915-6884620

(This space for State Use)

ORIGINAL DEPOSITED BY JERRY NELSON

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

OCT 07 1992