to Appropriate District Office

State of New Mexico Form C-103 Submit 3 Copies Energy, Minerals and Natural Resources Department Revised 1-1-89 OIL CONSERVATION DIVISION DISTRICT I P.O. Box 1980, Hobbs, NM 88240 WELL API NO. P.O. Box 2088 30-025-31487 Santa Fe, New Mexico 87504-2088 5. Indicate Type of Lease P.O. Drawer DD, Artesia, NM 88210 STATE X FEE 6. State Oil & Gas Lease No. 1000 Rio Brazos Rd., Aztec, NM 87410 B-9613 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" WEST DOLLARHIDE DRINKARD UNIT (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: GAS WELL OEL WELL OTHER WATER INJECTION R. Well No. Name of Operator TEXACO EXPLORATION AND PRODUCTION INC. 120 9. Pool name or Wildcat 3. Address of Operator Midland, Texas 79702 P. O. Box 3109 DOLLARHIDE TUBB DRINKARD Well Location 2224 Feet From The WEST Unit Letter F : 2190 Feet From The NORTH Line Line and thip 24-SOUTH Range 38-EAST

10. Elevation (Show whether DF, RKB, RT, GR, etc.) County NMPM LEA 32 Township 24-SOUTH Section GR-3170', KB-3183' Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: **ALTERING CASING** REMEDIAL WORK PLUG AND ABANDON PERFORM REMEDIAL WORK COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT TEMPORARILY ABANDON **CHANGE PLANS** CASING TEST AND CEMENT JOB X **PULL OR ALTER CASING** OTHER: CORE & PRODUCTION CASING OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 1. DRILLED 11 INCH HOLE TO 3935'. REDUCE HOLE SIZE TO 7 7/8. CUT NINE CORES: 6465-6525, REV. 60'. 6525-6569, RECV. 44'. 6569-6593, RECV. 24'. 6593-6615, RECV. 22'. 6665-6698, RECV. 33'. 6698-6714, RECV. 16'. 6714-6774, RECV. 60'. 6774-6810, RECV. 36'. 6810-6834, RECV. 7'. DRILLED TO 7495'. TD @ 3:30 PM 08-04-93. 2. HLS RAN GR-CSL-DLL-MSFL-CAL, GR-CSNG-CNL-SDL-DSN-CAL FROM 7495' TO 5000'. RAN SFT @ 6492', 6513' & 6434'. PULLED GR-DSN TO SURFACE. 3. RAN 112 JOINTS OF 5 1/2, 15.5#, WC-50, 31 JOINTS OF 17# WC-50 AND 39 JOINTS OF 17# L-80, LTC CASING SET @ 7495'. 4. DOWELL CEMENTED WITH 2350 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 PPG, 1.94 CF/S). F/B 425 SACKS CLASS H (15.6 PPG, 1.18 CF/S). PLUG DOWN @ 1:00 PM 08-06-93. CIRCULATED 157 SACKS. 5. ND. RELEASE RIG @ 4:30 PM 08-06-93.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. TITLE DRILLING OPERATIONS MANAGER _ DATE 08-11-93 TELEPHONE NO. 915-6884620 TYPE OR PRINT NAME C.P. BASHAM (This space for State Use) Orig. Signed by AUG 17 1993 Paul Kautz

... TIBLE -

- DATE

Geologist

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY -

6. PREP TO COMPLETE.