

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
30-025-31975

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
B-9613

7. Lease Name or Unit Agreement Name  
WEST DOLLARHIDE DRINKARD UNIT

8. Well No.  
128

9. Pool name or Wildcat  
DOLLARHIDE TUBB DRINKARD

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator  
TEXACO EXPLORATION AND PRODUCTION INC.

3. Address of Operator  
P. O. Box 3109 Midland, Texas 79702

4. Well Location  
Unit Letter D : 1310 Feet From The NORTH Line and 150 Feet From The WEST Line

Section 33 Township 24-SOUTH Range 38-EAST NMPM LEA County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
GR-3195', KB-3208'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: PRODUCTION CASING ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. DRILLING 11 INCH HOLE TO 3948'. REDUCED HOLE SIZE TO 7 7/8. DRILLED TO 7625'. TD @ 6:00 AM 07-29-93.
2. HLS RAN GR-DLL-MSFL-CSL, GR-CSNG-SDL-DSN FROM 7609' TO 5000'. PULLED GR-DSN TO SURFACE.
3. RAN 111 JOINTS OF 5 1/2, 15.5# WC-50, 29 JOINTS OF 17#, WC-50 AND 41 JOINTS OF 17#, L-80, LTC CASING SET @ 7625'.
4. DOWELL CEMENTED WITH 2100 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 PPG, 1.94 CF/S). F/B 500 SACKS CLASS H (15.6 PPG, 1.18 CF/S). PLUG DOWN @ 10:54 PM 07-30-93. CIRCULATED 520 SACKS.
5. ND. RELEASE RIG @ 11:45 AM 07-31-93.
6. PREP TO COMPLETE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE C.P. Basham / SDH TITLE DRILLING OPERATIONS MANAGER DATE 08-03-93

TYPE OR PRINT NAME C.P. BASHAM

TELEPHONE NO. 915-6884620

(This space for State Use)

Orig. Signed by  
Paul Kautz  
Geologist

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

AUG 09 1993