Submit 3 Copies to Appropriate District Office

CONDITIONS OF APPROVAL, IF ANY:

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

District Office	
DISTRICT I P.O. Box 1980, Hobbe, NM \$8240 DISTRICT II P.O. Drawer DD, Artesia, NM \$8210 OIL CONSERVATION DIVISION P.O. Box 2088 Santa Fe, New Mexico 87504-2088	WELL API NO. 30-025-32014
	5. Indicate Type of Lease STATE X FEE
DISTRICT III 1000 Rio Brazos Rd., Aziac, NM 87410	6. State Oil & Gas Lesse No. B-9613
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
	7. Lease Name or Unit Agreement Name WEST DOLLARHIDE DRINKARD UNIT
I. Type of Well: OL X CAS WELL OTHER	
2. Name of Operator TEXACO EXPLORATION AND PRODUCTION INC.	8. Well No.
3. Address of Operator P. O. Box 3109 Midland, Texas 79702	9. Pool same or Wildox
4. Well Location	DOLLARHIDE TUBB DRINKARD
Unit Letter H : 1420 Feet From The NORTH Line and _	1250 Feet From The EAST Line
Section 32 Township 24-SOUTH Range 38-EAST	NMPM LEA County
10. Elevation (Show whether DF, RKB, RT, GR, et GR-3191'	(c.)
Check Appropriate Box to Indicate Nature of Notice	ce. Report, or Other Data
• • • • • • • • • • • • • • • • • • •	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOF	RK ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DE	RILLING OPNS. DPLUG AND ABANDONMENT
PULL OR ALTER CASING X CASING TEST A	AND CEMENT JOB
OTHER: CHANGE SUFFACE CASING SIZE X OTHER:	
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent date work) SEE RULE 1103.	ss, including estimated date of starting any proposed
REVISED SURFACE CASING: SET 8 5/8 INCH, 24#, WC-50, STC CASING AT SACKS CLASS C w/ 4% GEL, 2% CACL2 (13.5ppg, 1.74cf/s, 9.11gw/s). 8ppg, 1.34cf/s, 6.31gw/s).	1210' AND CEMENT TO SURFACE WITH 500 F/B 200 SACKS CLASS C w/ 2% CACL2 (14.
NO INTERMEDIATE CASING WILL BE SET.	
REVISED CEMENT FOR PRODUCTION CASING: 1500 SACKS 35/65 POZ CLASS (12.8ppg, 1.94cf/s, 10.46gw/s). F/B 500 SACKS CLASS H (15.6ppg, 1.94cf/s)	S H w/ 6% GEL, 5% SALT, 1/4# FLOCELE .18cf/s, 5.2gw/s).
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SIGNATURE C. P. Basham / S. W. TITLE DRILLING OF	PERATIONS MANAGER DATE 07-28-93
TYPE OR PRINT NAME C. P. BASHAM	ТЕ ДЕРНО МЕ NO. 915-68846
(This space for State Use) Orig. Signed by Paul Kautz	AUG 02 1993
Coologist	DATE