Form 3160-5 (July 1989) (Formerly 9

16.

## UNI: STATES

CONTACT RECEIVIN OFFICE FOR NUMBER OF COPIES REQUIRED (Other instructions on reverse BLM Roswell District Modified Form No.

	MM060-31	5U-4				
į	LEASE DESIGN	ATION	NO 4	ERIÀ	L NO	 •

004)	DEPARTMENT	OF THE	INTERIO
-331)	DUDEALLOE LA	NID MANIA	CEMENT

BURE	AU OF LAND MANAGEMEN			
(Do not use this form for propo	TICES AND REPORT sals to drill or to deepen or plug ATION FOR PERMIT—" for such prope	DECK ED & University lesselvos.	6 if model Accorded	CESE SEZ40
1. OIL X GAS OTHER			7. UNIT AGREEMENT NAM COOPER JAL UNIT	-
2. NAME OF OPERATOR TEXACO EXPLORATION AN	8. FARM OR LEASE NAMI			
3. ADDRESS OF OPERATOR		3a. AREA CODE & PHONE NO.	9. WELL NO.	
	and, TX 79702	(915) 688-4620	403	
4. LOCATION OF WELL (Report location See also space 17 below.)		10. FIELD AND POOL, OR WILDCAT  LANGLIE MATTIX SR-QN		
150' FNL & 100' FWL, UNIT	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA			
			SEC. 19, T-24-	S, R-37-E
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)			12. COUNTY OR PARISH	13. STATE
API #30 025 32286 GR-3308', KB-3318'			LEA	NM


Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

TEST WATER SHUT-OFF	Ш	PULL OR ALTER CASING	Н	WATER SHUT-OFF	Ш	REPAIRING WELL		
FRACTURE TREAT	Ш	MULTIPLE COMPLETE	Ш	FRACTURE TREATMENT	Щ	ALTERING CASING		
SHOOT OR ACIDIZE		ABANDON*	Ш	SHOOTING OR ACIDIZING		ABANDONMENT*		
REPAIR WELL	П	CHANGE PLANS		(Other) PRODUCTION			X	
(Other)				(NOTE: Report result Completion or Rec	its of omple	multiple completion on Well trion Report and Log form.)		

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this
- 1. DRILLED TO 2995'. CORED 2995'-3055', REC. 60'. CORED 3055'-3115', REC. 60'. CORED 3115'-3175', REC. 60'. CORED 3175'-3235', REC. 60'. DRILLED TO 3750'. TD @ 10:30 AM 11-20-93.
- 2. HLS RAN GR-DSN-SDL-CSNG, GR-DLL-MSFL, GR-FWS FROM 3749' TO 2700'. PULLED GR-DSN TO 100'.
- 3. RAN 87 JTS OF 5\_1/2, 15.5#, WC-50, LTC CASING SET @ 3750'. RAN 10 CENTRALIZERS.
- 4. DOWELL CEMENTED WITH 600 SACKS 35/65 POZ CLASS H w/ 6% GEL, 5% SALT, 1/4# FLOCELE @ 12.8PPG. F/B 350 SACKS CLASS H w/ 1% CACL2 @ 15.6PPG. PLUG DOWN @ 10:30 AM 11-21-93. CIRCULATED 165 SACKS.
- 5. ND. RELEASE RIG @ 3:30 PM 11-21-93.

MOTICE OF INTENTION TO:

6. PREP TO COMPLETE.



SUBSEQUENT REPORT OF:

18. I hereby certify that the foregoing is true and correct				
SIGNED C. P. Basham/CWH	TITLE	DRILLING OPERATIONS MANAGER	DATE	11-22-93
(This space for Federal or State office use)				
APPROVED BY	TITLE		DATE	