Form 3160-5 (June 1990)

UI.. ED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

N.M. OIL CONS. COMMISSION
P.O. JX 1980 | FORM APPROVED
HORBS NEW MEXICO 882400

BUREAU OF LAND MANAGEMENT			Expires: March 31, 1993
		5. Lease Designation and Serial No.	
SUNDRY NOTICES AND REPORTS ON WELLS			LC 032582-B
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.			6. If Indian, Allottee or Tribe Name
Use "APPLICATION FOR PERMIT -" for such proposals			
SUBMIT ORIGINAL PLUS 5 COPIES 1. Type of Well			7. If Unit or CA, Agreement Designation
X Oil Gas Other 2. Name of Operator			8. Well Name and No. Wells B-1 #7
Prime Operating Company		9. API Well No.	
3. Address and Telephone No.		30-025-32756	
731 W. Wadley, Bldg. L-220, Midland, TX 79705			10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or	r Survey Description)		Jalmat (Tnsl, Yts, 7 Rvrs) 11. County or Parrish, State
Sec. 1, T-25S, R-36-E 1930' FNL & 1780' FEL			
			Lea, N.M.
	BOX(s) TO INDICATE N		REPORT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
Notice of Intent	Abandonment		Change of Plans
	Recompletion		New Construction
x Subsequent Report	Plugging Back		Non-Routine Fracturing
Office About annual Nation	Casing Repair		Water Shut-Off
Final Abandonment Notice	Altering Casing	tting of	Conversion to Injection
	X Other: Spud and se surface casing	-	Dispose Water (Note: Report results of multiple completion on Well
	Surface casing		Completion or Recompletion Report and Log form.)
any proposed work. If well is directionally drilled, pertinent to this work.) 1. Spud 12 1/4" hole @ 10:30 p.m. on 12-18-94. 2. Drill to 1217'. 3. On 12-19-94 ran 28 jts. of 8 5/8" J-55, 24#, S 4. Cemented with 400 sxs Premium Plus w/4% (5). Ran Temperature Survey, found TOC @ 120'6. RIH with 1" tubing down 8 5/8" annulus to 120'7. Circulated cement to surface, circ. approx. 25'8. Cut off casing and weld on 8 5/8" wellhead. 9. WOC 12 3/4 Hr. 10. NU BOP & test casing to 1000# for 30 minute 11. Resumed drilling 7 7/8" hole. 12. Above operations witnessed by representative	T&C casing, using 9 centralizers. Cacl@ & 1/4# flocele. Cement did . Y, cemented with 75 sxs. Premium sxs cement to pit. es, tested OK.	not circulate. Plus cement.	s for all markers and zones
14. I hereby certify that the foregoing is true and	correct		
signed the land Title: Engineering assistant Date: 1-18-95			
(This space for Federal or State office use)			
Approved by	Title:		Date:
Approved by Conditions of approval, if any:	Title:		Jaic.