

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.

30 025 32769

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil / Gas Lease

7. Lease Name or Unit Agreement Name

WEST DOLLARHIDE DRINKARD UNIT

8. Well No.

112

9. Pool Name or Wildcat

DOLLARHIDE TUBB DRINKARD

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐

b. Type of Completion:

NEW WELL ☒ WORKOVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RES. ☐ OTHER ☐

2. Name of Operator

TEXACO EXPLORATION & PRODUCTION INC.

3. Address of Operator

P.O. BOX 730, HOBBS, NM 88240

4. Well Location

Unit Letter L : 1475 Feet From The SOUTH Line and 790 Feet From The WEST Line

Section 32 Township 24-S Range 38-E NMPM LEA COUNTY

10. Date Spudded

2/25/95

11. Date T.D. Reached

3/10/95

12. Date Compl. (Ready to Prod.)

4/2/95

13. Elevations (DF & RKB, RT, GR, etc.)

3144'

14. Elev. Csghead

15. Total Depth

7412'

16. Plug Back T.D.

7362'

17. If Mult. Compl. How Many Zones?

1

18. Intervals

Drilled By

Rotary Tools

0'-7412'

Cable Tools

19. Producing Interval(s), of this completion - Top, Bottom, Name

6428'-6443', DRINKARD; 6550'-7324', ABO

20. Was Directional Survey Made

YES

21. Type Electric and Other Logs Run

GR-DLL-MSFL-BHCS-CAL

22. Was Well Cored

NO

23.

CASING RECORD (Report all Strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENT RECORD	AMOUNT PULLED
8 5/8	24#	1176'	11	525 SACKS	
5 1/2	15.5#, 17#	7412'	7 7/8	2266 SACKS	

24.

LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN
NONE				

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2-7/8"	6369'	NONE

26. Perforation record (interval, size, and number)

6428'-6443', 6 JSPF, 96 HOLES
6550'-7324', 2 JSPF, 382 HOLES

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
6428'-6443'	52584G XLG FLUID+169072# 20/40 SAND
6550'-7324'	14000G 15% HCL

28.

PRODUCTION

Date First Production 4/2/95		Production Method (Flowing, gas lift, pumping - size and type pump) PUMP (2.5" X 2" X 22')					Well Status (Prod. or Shut-In) PRODUCING	
Date of Test 4/4/95	Hours tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl. 137	Gas - MCF 144	Water - Bbl. 617	Gas - Oil Ratio 1051	
Flow Tubing Press.	Casing Pressure	Calculated 24- Hour Rate	Oil - Bbl. 137	Gas - MCF 144	Water - Bbl. 617	Oil Gravity - API -(Corr.) 38.5		

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

SOLD

Test Witnessed By

D. E. WELBORN

30. List Attachments DEVIATION SURVEY

31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Engineering Assistant

DATE 5/3/95

TYPE OR PRINT NAME

Darrell J. Carriger

Telephone No. 397-0426

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	1175	T. Canyon
T. Salt	1371	T. Strawn
B. Salt	2510	T. Atoka
T. Yates	2640	T. Miss
T. 7 Rivers		T. Devonian
T. Queen	3564	T. Silurian
T. Grayburg		T. Montoya
T. San Andres	3948	T. Simpson
T. Glorieta	5029	T. McKee
T. Paddock		T. Ellenburger
T. Blinebry		T. Gr. Wash
T. Tubb	5954	T. Delaware Sand
T. Drinkard	6222	T. Bone Springs
T. Abo	6520	T.
T. Wolfcamp		T.
T. Penn		T.
T. Cisco (Bough C)		T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 6222 to 6520
No. 2, from 6520 to 7412

No. 3, from to
No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from to feet
No. 2, from to feet
No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	1175	1175	SNDSTN, SHALE				
1175	1371	196	ANHY, SALT, SHALE				
1371	2510	1139	SALT, ANHY, SHALE				
2510	2640	130	ANHY, SNDSTN, DOL				
2640	3564	924	ANHY, SNDSTN, DOL				
3564	3948	384	ANHY, SNDSTN, DOL				
3948	5029	1081	DOL				
5029	5954	925	DOL, SNDSTN				
5954	6222	268	DOL, SNDSTN				
6222	6520	298	DOL, SNDSTN				
6520	7412	892	DOL, SNDSTN				