

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. OIL CONS. COMMISSION
P. BOX 1980
HOBBS, NEW MEXICO 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Enron Oil & Gas Company

3. Address and Telephone No

P. O. Box 2267, Midland, Texas 79702

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1430' FSL & 1830' FEL
Section 1, T25S, R33E

5. Lease Designation and Serial No.

NM 19859

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Hallwood 1 Federal #3

9. API Well No.

30 025 32886

10. Field and Pool, or Exploratory Area

Red Hills Bone Spring

11. County or Parish, State

Lea County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Csg test & cmt job
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

3-5-95 - Spud 10:15 a.m.

Ran 15 joints 11-3/4" 42# H-40 ST&C casing set at 672'.

Cemented with 250 sx Prem + cmt, 2% CC, 4% gel, 1/4# FC; 13 ppg, 1.93 cuft/sx, 86 bbls slurry. And 100 sx Prem + cmt, 2% CC; 14/5 ppg, 1.32 cuft/sx, 23 bbls. Circulated 66 sacks cement.

WOC - 9-1/4 hours. 30 minutes pressure tested to 600 psi, OK.

3-8-95 - Ran 20 jts 8-5/8" 32# FS-80 ST&C & 97 jts 32# K-55 ST&C casing set at 4950'.

Cemented with 400 sx HLP, 5# salt, 5# gel, 1/4# FC; 12.4 ppg, 2.104 cuft/sx, 150 bbls slurry and 800 sx HLP, 5# salt, 1/4# FC; 12.4 ppg, 2.040 cuft/sx, 291 bbls, and 200 sx HLP, 2% CC; 14.8 ppg, 1.320 cuft/sx, 47 bbls slurry. Circulated 155 sacks. WOC - 12-1/2 hours.

30 minutes pressure tested to 1000 psi, OK.

(OVER)

14. I hereby certify that the foregoing is true and correct

Signed Betty Gildon Betty Gildon Title Regulatory Analyst

Date

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

ACCEPTED FOR RECORD
Date J. Lara
APR 20 1995

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

CARLSBAD, NEW MEXICO

3-20-95 - TD 12,550'

3-22-95 - Ran 143 jts 5-1/2" 17# CF-95 LT&C casing and 149 jts 5-1/2" 17# P-110 LT&C casing set at 12,538'.

Cemented with 500 sx Prem Cement, 3% Econ, 5# salt, 5# gtl, 1/4# FC;
11.5 ppG, 2.860 cuft/sx, 255 bbls; and 456 sx Prem, 3% Econ, 5# salt, 1/4# FC;
11.5 ppG, 2.847 cuft/sx, 231 bbls; and 185 sx Prem 50/50 poz, 2% gel, 3% KCl,
.5% Halad-322; 14.4 ppG, 1.256 cuft/sx, 41 bbls slurry.

WOC - 12 hours
30 minutes pressure tested to 2300 psi, OK.