

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies

State of New Mexico

Ene . . . Minerals and Natural Resources Department

Form C-105

Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-32911
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil / Gas Lease	

WELL COMPLETION OR RECOMPLETION REPORT AND LOG															
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐					7. Lease Name or Unit Agreement Name STATE 'L'										
b. Type of Completion: NEW WELL ☒ WORKOVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RES. ☐ OTHER ☐															
2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC.					8. Well No. 5										
3. Address of Operator P.O. BOX 730, HOBBS, NM 88240					9. Pool Name or Wildcat JUSTIS BLINEBRY										
4. Well Location Unit Letter F ; 2260 Feet From The NORTH Line and 1800 Feet From The WEST Line Section 2 Township 25-S Range 37-E NMPM LEA COUNTY															
10. Date Spudded 4/29/95		11. Date T.D. Reached 5/10/95		12. Date Compl. (Ready to Prod.) 6/13/95		13. Elevations (DF & RKB, RT, GR, etc.) 3165'GR., 3175'KB		14. Elev. Csghead							
15. Total Depth 7240'		16. Plug Back T.D. 7137'		17. If Mult. Compl. How Many Zones?		18. Intervals Drilled By 0'-7240'		Rotary Tools Cable Tools							
19. Producing Interval(s), of this completion - Top, Bottom, Name 5202-5321;5487-5768;5920-6021;6158-6263								20. Was Directional Survey Made NO							
21. Type Electric and Other Logs Run GR-DLL-MSFL-BHCS-CAL;CSNG-CNL-LDT-CAL;GR-CNL								22. Was Well Cored NO							
23. CASING RECORD (Report all Strings set in well)															
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENT RECORD		AMOJNT PULLED					
8 5/8"		24#		985'		11"		525 SX CIC, CIR 275 SX							
5 1/2"		15.5 & 17#		7240'		7 7/8"		1900 SX CIH							
24. LINER RECORD										25. TUBING RECORD					
SIZE		TOP		BOTTOM		SACKS CEMENT		SCREEN		SIZE		DEPTH SET		PACKER SET	
NONE										2-7/8"		5165'			
26. Perforation record (interval, size, and number) 5202'-5321', 2 JSPF, 66 HOLES; UPPER BLINEBRY 5487'-5768', 2 JSPF, 136 HOLES; LOWER BLNBRY 5920'-6021', 2 JSPF, 108 HOLES; TUBB 6158'-6263', 2 JSPF, 100 HOLES, DRINKARD (PRODUCING ONLY FROM BLINEBRY PERFS)										27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.					
										DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED			
										5202-5321		8500G15%			
										5487-5768		2000G15%,F29000GXL,12000#SD			
										5920-6021		3000G15%160BSF/34000GXL128000#16/30			
28. PRODUCTION 6158-6263										3000G 15%, F54,600G FLD, 129000#SD					
Date First Production 6/13/95		Production Method (Flowing, gas lift, pumping - size and type pump) PUMP(2.5"X1.75"X26")								Well Status (Prod. or Shut-in) PRODUCING					
Date of Test 7/5/95		Hours tested 24		Choke Size 13/64"		Prod'n For Test Period		Oil - Bbl. 74		Gas - MCF 265		Water - Bbl. 204		Gas - Oil Ratio 3581	
Flow Tubing Press.		Casing Pressure		Calculated 24-Hour Rate		Oil - Bbl.		Gas - MCF		Water - Bbl.		Oil Gravity - API (Corr.) 38.6			
29. Disposition of Gas (Sold, used for fuel, vented, etc.) SOLD										Test: Witnessed By R. D. STEPHENS					
30. List Attachments DEVIATION SURVEY															
31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief.															
SIGNATURE <i>M. Angie Davila</i> TITLE Clerk										DATE 8/2/95					
TYPE OR PRINT NAME M. Angie Davila										Telephone No. 337-0443					

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	928'	T. Canyon	
T. Salt	1118'	T. Strawn	
B. Salt	2263'	T. Atoka	
T. Yates	2428'	T. Miss	
T. 7 Rivers	2689'	T. Devonian	6969'
T. Queen	3116'	T. Silurian	7240' TD
T. Grayburg	3433'	T. Montoya	
T. San Andres	3596'	T. Simpson	
T. Glorieta	4783'	T. McKee	
T. Paddock	5016'	T. Ellenburger	
T. Blinebry	5147'	T. Gr. Wash	
T. Tubb	5870'	T. Delaware Sand	
T. Drinkard	6041'	T. Bone Springs	
T. Abo	6263'	T.	
T. Wolfcamp		T.	
T. Penn		T.	
T. Cisco (Bough C)		T.	

Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 5202' to 5321'

No. 2, from 5487' to 5768'

No. 3, from 5920' to 6021'

No. 4, from 6158' to 6263'

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from to feet

No. 2, from to feet

No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0'	928'	928'	SANDSTONE, SHALE	6969'	7240'	271'	LIMESTONE, DOLOMITE
928'	1118'	190'	ANHY, SHALE, SALT				
1118'	2263'	1145'	SALT, ANHY, SHALE				
2263'	2428'	165'	ANHY, DOLOMITE				
2428'	2689'	261'	ANHY, SANDSTONE, DOLO				
2689'	3116'	427'	DOLOMITE, SANDSTONE				
3116'	3433'	317'	SANDSTONE, DOLOMITE				
3433'	3596'	163'	DOLOMITE, SANDSTONE				
3596'	4783'	1187'	DOLOMITE				
4783'	5016'	233'	SANDSTONE, DOLOMITE				
5016'	5147'	131'	DOLOMITE				
5147'	5870'	723'	DOLOMITE, SANDSTONE				
5870'	6041'	171'	DOLOMITE, SANDSTONE				
6041'	6263'	222'	DOLOMITE, LIMESTONE				
6263'	6969'	706'	DOLOMITE, LIMESTONE				