

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. OIL CONS. COMMISSION
P.O. BOX 1980
HOBBS, NEW MEXICO 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT --" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well: ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator
TEXACO EXPLORATION & PRODUCTION INC.

3. Address and Telephone No. P.O. Box 2100, Denver Colorado 80201 (303)621-4851

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit Letter F 2310 Feet From The NORTH Line and 1650 Feet From The

WEST Line Section 35 Township 24-S Range 37-E

5. Lease Designation and Serial No.
NM14218

6. If Indian, Alottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and Number
C. C. FRISTOE 'B' FEDERAL NCT-2

17

9. API Well No.
30-025-33383

10. Field and Pool, Exploratory Area
JUSTICE BLINEBRY, JUSTIS TUBB DRINKARD, ABO

11. County or Parish, State
LEA, NEW MEXICO

12. Check Appropriate Box(s) To Indicate Nature of Notice, Report, or Other Data

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ OTHER: SPUD, SURF CSG, PROD CSG.
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- NABORS SPUD 11 INCH HOLE @ 7:00 PM 06-01-96. DRILLED TO 1008'. TD @ 1:30 PM 06-02-96.
- RAN 2 JOINTS OF 8 5/8 INCH, 24#, WC-50, 4 JOINTS OF 8 5/8 INCH, 24#, WC-50, 17 JOINTS OF 8 5/8 INCH, 24, K-55, STC CASING SET @ 1012'. RAN 6 CENTRALIZERS.
- DOWELL CEMENTED WITH 325 SACKS CLASS C W/ 2% GEL, 4% CACL2 (13.5 PPG, 1.74 CF/S). F/B 200 SACKS CLASS C W/ 2% CACL2 (14.6 PPG, 1.32 CF/S). PLUG DOWN @ 6:45 PM 06-02-96. CIRCULATED 10 SACKS.
- NU BOP & TESTED TO 1200#. TESTED CASING TO 1200# FOR 30 MINUTES FROM 7:15 AM TO 8:00 AM 06-03-96.
- WOC TIME 12-1/2 HOURS FROM 6:45 PM 06-02-96 TO 7:15 AM 06-03-96.
- DRILLING 7 7/8 INCH HOLE.
- DRILLED 7 7/8 INCH HOLE TO 6450'. TD @ 3:15 AM 06-13-96.
- HLS RAN NGT-CNL-LDT, 6434'-1000', GR-CNL TO SURFACE. NGT-DLL-MSFL 6434'-2300', NGT-BHC 6434'-2300'.
- RAN 48 JOINTS OF 5 1/2 INCH, 17#, WC-70 AND 102 JOINTS (4372') OF 15.5# WC-50, LTC CASING SET @ 3988'. DV TOOL @ 3988'.
- DOWELL CEMENTED: 1ST STAGE - 605 SKS 50/50 POZ CLASS H W/ 2% GEL, 5% SALT, 1/4# FLOCELE (14.2 PPG, 1.35 CF/S). OPEN DV TOOL. CIRC 104 SKS. 2ND STAGE - 1200 SKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 PPG, 1.94 CF/S). F/B 100 SACKS CLASS H NEAT (15.6 PPG, 1.18 CF/S). PLUG DOWN @ 7:25 PM 06-14-96. CIRCULATED 286 SACKS.
- ND. RELEASE RIG @ 1:45 AM 06-15-96.
- PREP TO COMPLETE.

14. I hereby certify that the foregoing is true and correct

SIGNATURE C.P. Basham / SRH TITLE Eng. Assistant.

DATE 6/25/96

TYPE OR PRINT NAME Sheilla D. Reed-High

(This space for Federal or State office use)

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.