

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Div
P.O. Box 1980
Hobbs, NM 8824

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT --" for such proposals

5. Lease Designation and Serial No.
NM-LC 057509

6. If Indian, Allottee or Tribe Name

7. If Unit or CA Agreement Designation

8. Well Name and Number
ERWIN G.L. 'B' FEDERAL

9. API Well No.
30-025-33384

10. Field and Pool Exploratory Area
JUSTIS DORY, JUSTIS TUBB DRINKARD ABO

11. County or Parish, State
LEA, NEW MEXICO

SUBMIT IN TRIPLICATE

1. Type of Well: ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator
TEXACO EXPLORATION & PRODUCTION INC

3. Address and Telephone No.
P.O. Box 2100, Denver Colorado 80201 (303)621-4851

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
Unit Letter P : 900 Feet From The SOUTH Line and 990 Feet From The
EAST Line Section 35 Township 24-S Range 37-E

Check Appropriate Box(s) To Indicate Nature of Notice, Report, or Other Data

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ OTHER: COMPLETION

TYPE OF ACTION

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion or Well Completion or Recompletion Report and Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- HALLIBURTON PERF 5-1/2" CASING W/ 2 JSPF: 6113'-6121', 6124'-6130', 6136'-6142', 6150'-6155', 6166'-6178', 6186'-6190. 82 HOLES. RAN 5-1/2" PKR. 2.5" SN. X-OVER. 193 jts. 3 1/2" 12.95# FRAC TBG. TESTED IN @10,000 PSI. SET PKR @ 6043'. 06-08-96
- DOWELL ACIDIZED DRINKARD PERFS: 6113'-6190' W/3000 GALS 15% NEFE. 82 HOLES. REL PKR. RESET PKR. 06-11-96.
- DOWELL FRAC 5.5 CSG PERFS: 6113'-6190' @ JUSTIS DRINKARD ZONE W/ 38,000 GAL XL GEL & 104,360# 20/40 SAND. 06-13-96.
- RU DOWELL COIL TBG UNIT. CLEAN OUT FRAC SAND FROM 2485' TO 6350'. REL PKR. 06-16-96.
- RU HALLIBUTRON. SET WL RBP @ 5755'. TEST CSG TO 3000 PSI. SPOT 10' SAND ON RBP W/DUMP BAILER. PERF'D 5 1/2" CSG W/2 JSPF: 5171'-5174', 5190'-5195', 5229'-5234', 5261'-5267', 5303'-5306', 5325'-5328'-5350'-5353', 5359'-5364', 5414'-5424'. 86 HOLES. 06-19-96.
- DOWELL ACIDIZED VIA CSG BLINEBRY 'B' PERFS 5171'-5425' (86 HOLES) W/6500 GAL 15% NEFE. RU HALLIBURTON. SET WL RBP @ 5140'. TESTED CSG TO 3000 PSI. SPOT 10' SAND ON RBP. PERF'D BLINEBRY 'A' ZONE W/2JSPF @ 5018-5022', 5050'-5063', 5075'-5082', 5091'-5094', 5102'-5112', 45 HOLES. 06-20-96.
- DOWELL ACIDIZED BLINEBRY 'A' ZONE PERFS 5018'-5112' (45 HOLES) W/2500 GAL 15% NEFE. 06-21-96.
- DOWELL FRAC'D BLINEBRY 'A' ZONE PERFS 5018'-5112' W/51,000 GAL 35# BORATE CROSS LINKED GEL CONTAINING 136,180# SAND AND 40,000 RESIN COATED SAND. 06-22-96.
- SET PKR @ 70'. PULL PKR. RAN 3.5" ANCHOR W/PURGE VALVE. 2.5" SN. 2-7/8" TBG. JTS. TUBING ANCHOR REMOVE BOP & LAND MUD ANCHOR @ 6299' W/SN @ 6247'. RUN RODS. 06-29-96.
- HOOK UP FLOWLINE. 06-30-96.
- ON PRODUCTION @ 9:00 A.M. 07-01-96.
- PUMPED 68 BO. 371 BW. 441 MCF IN 24 HOURS. 07-17-96.

14. I hereby certify that the foregoing is true and correct.

SIGNATURE C.P. Basham / SEH TITLE Eng. Assistant

DATE 7/31/96

TYPE OR PRINT NAME Sheilla D. Reed-High

(This space for Federal or State office use.)

APPROVED

CONDITIONS OF APPROVAL, IF ANY: TITLE

DATE

Title 18 U.S.C. Section 1001 makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

RECORDED FOR RECORD
JUL 31 1996
BLS