

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-33404
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil / Gas Lea	

WELL COMPLETION OR RECOMPLETION REPORT AND LOG															
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____					7. Lease Name or Unit Agreement Name WEST DOLLARHIDE DRINKARD UNIT										
b. Type of Completion: NEW WELL ☒ WORKOVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RES. ☐ OTHER _____															
2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC.					8. Well No. 157										
3. Address of Operator 205 E. Bender, HOBBS, NM 88240					9. Pool Name or Wildcat DOLLARHIDE TUBB DRINKARD										
4. Well Location Unit Letter <u>P</u> ; <u>1275</u> Feet From The <u>SOUTH</u> Line and <u>400</u> Feet From The <u>EAST</u> Line Section <u>31</u> Township <u>24-S</u> Range <u>38-E</u> NMPM _____ LEA COUNTY															
10. Date Spudded 9/20/96		11. Date T.D. Reached 10/2/96		12. Date Compl. (Ready to Prod.) 10/18/96		13. Elevations (DF & RKB, RT, GR, etc.) 3133'		14. Elev. Csghead							
15. Total Depth 6935'		16. Plug Back T.D. 6924'		17. If Mult. Compl. How Many Zones?		18. Intervals Drilled By PRIDE		Rotary Tools Cable Tools							
19. Producing Interval(s), of this completion - Top, Bottom, Name 6376'-6880' DRINKARD-ABO								20. Was Directional Survey Made YES							
21. Type Electric and Other Logs Run GR-DLL-MSFL-BHC-CMR-CCL								22. Was Well Cored NO							
23. CASING RECORD (Report all Strings set in well)															
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENT RECORD		AMOUNT PULLED					
8 5/8		24#		1200'		11		550 SACKS							
5 1/2		15.5 & 17#		6935'		7 7/8		1729 SACKS							
24. LINER RECORD										25. TUBING RECORD					
SIZE		TOP		BOTTOM		SACKS CEMENT		SCREEN		SIZE		DEPTH SET		PACKER SET	
										2-7/8"		6900'			
26. Perforation record (interval, size, and number) 6376'-6499' W/2JSPF .50" HOLES 6586'-6880' W/2JSPF .50" HOLES										27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.					
										DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED			
										6376'-6499'		ACID W/6500 GALS 15% NEFE HCL			
										6586'-6880'		ACID W/3500 GALS 15% NEFE HCL			
28. PRODUCTION															
Date First Production 10/18/96		Production Method (Flowing, gas lift, pumping - size and type pump) PUMPING (2.5" X 1.5" X 26')								Well Status (Prod. or Shut-in) PRODUCING					
Date of Test 10-20-96		Hours tested 24		Choke Size		Prod'n For Test Period		Oil - Bbl. 142		Gas - MCF 126		Water - Bbl. 54		Gas - Oil Ratio 887	
Flow Tubing Press.		Casing Pressure		Calculated 24-Hour Rate		Oil - Bbl.		Gas - MCF		Water - Bbl.		Oil Gravity - API -(Corr.)			
29. Disposition of Gas (Sold, used for fuel, vented, etc.) SOLD										Test Witnessed By TVS					
30. List Attachment DEVIATION SURVEY															
31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief.															
SIGNATURE <u>Paula S. Ives</u>		TITLE <u>Engineering Assistant</u>								DATE <u>12/9/96</u>					
TYPE OR PRINT NAME Paula S. Ives										Telephone No. 397-0432					

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	1154'	T. Canyon
T. Salt	1346'	T. Strawn
B. Salt	2515'	T. Atoka
T. Yates	2647'	T. Miss
T. 7 Rivers	2922'	T. Devonian
T. Queen	3570'	T. Silurian
T. Grayburg	3803'	T. Montoya
T. San Andres	4002'	T. Simpson
T. Glorieta	5093'	T. McKee
T. Paddock		T. Ellenburger
T. Blinebry	5362'	T. Gr. Wash
T. Tubb	6011'	T. Delaware Sand
T. Drinkard	6172'	T. Bone Springs
T. Abo	6524'	T.
T. Wolfcamp		T.
T. Penn		T.
T. Cisco (Bough C)		T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from	6376'	to	6499'	No. 3, from		to	
No. 2, from	6586'	to	6880'	No. 4, from		to	

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from		to		feet
No. 2, from		to		feet
No. 3, from		to		feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	1154	1154	SANDSTONE, SHALE				
1154	1346	192	ANHYDRITE, SHALE, SALT				
1346	2515	1169	SALT, ANHYDRITE, SHALE				
2515	2647	132	ANHYDRITE, DOLOMITE				
2647	2922	275	ANHYDRITE, SANDSTONE				
2922	3570	648	DOLOMITE, SANDSTONE				
3570	3803	233	SANDSTONE, DOLOMITE				
3803	4002	199	DOLOMITE, SANDSTONE				
4002	5093	1091	DOLOMITE				
5093	5362	269	SANDSTONE, DOLOMITE				
5362	6011	649	DOLOMITE				
6011	6172	161	DOLOMITE, SANDSTONE				
6172	6524	352	DOLOMITE, SANDSTONE				