

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-33413
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil / Gas Lea	

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐				7. Lease Name or Unit Agreement Name WEST DOLLARHIDE DRINKARD UNIT	
b. Type of Completion: NEW WELL ☒ WORKOVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RES. ☐ OTHER ☐					
2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC.				8. Well No. 156	
3. Address of Operator 205 E. Bender, HOBBS, NM 88240				9. Pool Name or Wildcat DOLLARHIDE TUBB DRINKARD	
4. Well Location Unit Letter <u>I</u> : <u>2000</u> Feet From The <u>SOUTH</u> Line and <u>1200</u> Feet From The <u>EAST</u> Line Section <u>32</u> Township <u>24-S</u> Range <u>38-E</u> NMPM <u>LEA</u> COUNTY					
10. Date Spudded 9/4/96	11. Date T.D. Reached 9/17/96	12. Date Compl. (Ready to Prod.) 10/2/96	13. Elevations (DF & RKB, RT, GR, etc.) 3164'	14. Elev. Csghead	
15. Total Depth 7200'	16. Plug Back T.D. 7150'	17. If Mult. Compl. How Many Zones?	18. Intervals Drilled By PRIDE	Rotary Tools Cable Tools	
19. Producing Interval(s), of this completion - Top, Bottom, Name 6452'-7114' DRINKARD-ABO				20. Was Directional Survey Made YES	
21. Type Electric and Other Logs Run PE-CN-L-D-NGT-NGR-BCS				22. Was Well Cored NO	

23. CASING RECORD (Report all Strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENT RECORD	AMOUNT PULLED
8 5/8	24#	1175'	11	525 SACKS	
5 1/2	15.5 & 17#	7200'	7 7/8	1800 SACKS	

24. LINER RECORD				25. TUBING RECORD			
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2-7/8"	7119'	

26. Perforation record (interval, size, and number) 6452'-6554' W/2JSPF 76 HOLES 6659'-7114' W/2JSPF 114 HOLES		27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 6452'-6554' ACID W/5700 GALS 15% NEFE HCL 6659'-7114' ACID W/8500 GALS 15% NEFE HCL	
--	--	--	--

28. PRODUCTION							
Date First Production 10/2/96		Production Method (Flowing, gas lift, pumping - size and type pump) PUMPING (2.5" X 1.5" X 20')				Well Status (Prod. or Shut-in) PRODUCING	
Date of Test 11-12-96	Hours tested 24	Choke Size OPEN	Prod'n For Test Period	Oil - Bbl. 60	Gas - MCF 40	Water - Bbl. 179	Gas - Oil Ratio 667
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API -(Corr.)	

29. Disposition of Gas (Sold, used for fuel, vented, etc.) SOLD					Test Witnessed By TVS	
--	--	--	--	--	--------------------------	--

30. List Attachment DEVIATION SURVEY	
---	--

31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief.			
SIGNATURE <i>Paula S. Ives</i>	TITLE Engineering Assistant	DATE 12/9/96	
TYPE OR PRINT NAME Paula S. Ives		Telephone No. 397-0432	

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	1171'	T. Canyon
T. Salt	1363'	T. Strawn
B. Salt	2543'	T. Atoka
T. Yates	2674'	T. Miss
T. 7 Rivers	2960'	T. Devonian
T. Queen	3621'	T. Silurian
T. Grayburg	3869'	T. Montoya
T. San Andres	4094'	T. Simpson
T. Glorieta	5117'	T. McKee
T. Paddock		T. Ellenburger
T. Blinebry	5370'	T. Gr. Wash
T. Tubb	6046'	T. Delaware Sand
T. Drinkard	6248'	T. Bone Springs
T. Abo	6601'	T.
T. Wolfcamp		T.
T. Penn		T.
T. Cisco (Bough C)		T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from	6452'	to	6554'	No. 3, from	to
No. 2, from	6659'	to	7114'	No. 4, from	to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from	to	feet
No. 2, from	to	feet
No. 3, from	to	feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	1171	1171	SANDSTONE, SHALE				
1171	1363	192	ANHYDRITE, SHALE, SALT				
1363	2543	1180	SALT, ANHYDRITE, SHALE				
2543	2674	131	ANHYDRITE, DOLOMITE				
2674	2960	286	ANHYDRITE, SANDSTONE,				
2960	3621	661	DOLOMITE, SANDSTONE				
3621	3869	248	SANDSTONE, DOLOMITE				
3869	4094	225	DOLOMITE, SANDSTONE				
4094	5117	1023	DOLOMITE				
5117	5370	253	SANDSTONE, DOLOMITE				
5370	6046	676	DOLOMITE				
6046	6248	202	DOLOMITE, SANDSTONE				
6248	6601	353	DOLOMITE, SANDSTONE				