Form 3160-5 (June 1990)

(This space for Federal or State office use)

CONDITIONS OF APPROVAL, IF ANY:

representations as to any matter within its jurisdiction.

TITLE

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or

APPROVED

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. DivisionFORM APPROVED
P.O. Box 1980
Hobbs, NM 88241

Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals		5. Lease Designation and Serial No. NM -14218
		6. If Indian, Alottee or Tribe Name
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
ype of Well: OIL GAS OTHER		Well Name and Number C. C. FRISTOE 'B' FEDERAL NCT-2
2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC.		18
3. Address and Telephone No. P.O. Box 2100, Denver Colorado 80201 (303)621-4851		9. API Well No.
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		30-025-33543
Unit Letter J : 1480 Feet From The SOUTH Line and 1400 Feet From The		WILDCAT - ELLENBURGER, JUSTIS BLINEBRY, TUBB,
EAST Line Section 26	Township 24-S Range 37-E	11. County or Parish, State LEA , NM
12. Check Appropriate TYPE OF SUBMISSION Notice of Intent Subsequent Report	Box(s) To Indicate Nature of Notice, R Abandonment Recompletion Plugging Back Casing Repair	Report, or Other Data TYPE OF ACTION Change of Plans New Construction Non-Routine Fracturing Water Shut-Off
Final Abandonment Notice	Altering Casing OTHER: COMPLETION	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)
 If well is directionally drilled, give subsurface local PERFORATED A 4-WAY SHOT @ 6750'. TIH W/A BAKER CEMENT RETAINER AN FOUND TOP OF CEMENT W/CBL @ 380 PERF'D THE ELLENBERGER W/9533'-95 SPOT ACID (29 BBLS) 7 1/2% HCL NEFE WELL STARTED FLOWING FLOW TO TA RIH W/ 301 JTS OF 2-7/8" TBG TO 9502'. RIH W/GS ANCHOR (1.25" X 12'), PUMP 	554' W/ 2 JSPF. 42 HOLES. TIH W/ PKR. 10-16-96. ETO BOTTOM OF PKR @ 9570'. SET PKR @ 9439' ANK @ 30 PSI. 10-19-96. RAN MUD JT, 4' PERFORATED SUB, SN, 3 JTS OI (1.5"), RODS, KBARS. 10-23-96. Q 9485'. MOVE IN PUMPING UNIT. 10-24-96.	s and zones pertinent to this work,)*. @ 500 PSI. 10-12-96. DF 50/50 POZ 'H' CEMENT. 10-13-96. 1. 10-17-96.
	ACCEPTED FOR RECORD ROV 1 4 1996 BLM	May 4 10 22 MH 19 ROS COMPANY ROSS COMPANY R
14. I hereby certify that the foregoing is true and correct SIGNATURE C.P. Basham	\ S≳ N TI TLE Eng. Assistant.	DATE 10/30/96
	D. Reed-High	

DATE