

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. C Cons. Division
P.O. Box 1980
Hobbs, NM 88241

FORM APPROVED
Budget Bureau No 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

Lease Designation and Serial No.

NMNM97153

If Indian, Allottee or Tribe Name

If Unit or CA, Agreement Designation

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

BTA OIL PRODUCERS

3. Address and Telephone No.

104 South Pecos, Midland, TX 79701

915-682-3753

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 1980' FWL
Sec. 10, T25S, R33E

NE/SW

8. Well Name and No.

Vaca Draw, 9418 JV-P, #1

9. API Well No.

30-025-33639

10. Field and Pool, or Exploratory Area

Wildcat

11. County or Parish, State

Lea County New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☒ Altering Casing
☒ Other CSG
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

11-23-96: Depth 715', Cmt'd 13-3/8" csg @ 715' (16 jts 54.5# J55-STC)
w/580 sx. Cmt circ. WOC 8 hrs, Installed csg hd & BOP's - cleaned
out to shoe.

11-24-96: Tested BOP's & csg to 1500 psi for 30 min on fresh wtr. WOC 18 hrs total
then drld shoe, Drlg 11" hole.

12-1-96: Depth 5000', Cmt'd 8-5/8" 32 # J55 & FS 80 STC csg @ 5000 w/1925 sx,
Cmt circ, Set slips & cut off, Installed spool & BOP's, Tested BOP's
per BLM spec's. Cleaned out to shoe. Tested csg to 1500 psi for 30
mins on fresh wtr - OK, Tested shoe to 11 ppg EMW - OK. WOC 18 hrs
total.

12-3-96: Depth 5190', Drlg 7-7/8" hole.

ACCEPTED FOR RECORD

DEC 09 1996

BLM

14. I hereby certify that the foregoing is true and correct

Signed Dorothy Houghton Title Regulatory Administrator Date 12/3/96

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any: